



Hall Effect Thruster Interactions Data From the Russian Express-A2 and Express-A3 Satellites Acquire Express-A3 SPT-100 Based Propulsion Subsystem and Other Subsystem Flight Operation TM-Data for the Period of January 1, 2001 to and Including March 31, 2001, Task 32

N. Sitnikova, D. Volkov, I. Maximov, and V. Petrusevich
Nauchno-Proizvodstvennoe Obiedinenie Prikladnoi Mekhaniki, Krasnoyarsk region, Russia

D. Allen
Schafer Corporation, Chelmsford, Massachusetts

The NASA STI Program Office . . . in Profile

Since its founding, NASA has been dedicated to the advancement of aeronautics and space science. The NASA Scientific and Technical Information (STI) Program Office plays a key part in helping NASA maintain this important role.

The NASA STI Program Office is operated by Langley Research Center, the Lead Center for NASA's scientific and technical information. The NASA STI Program Office provides access to the NASA STI Database, the largest collection of aeronautical and space science STI in the world. The Program Office is also NASA's institutional mechanism for disseminating the results of its research and development activities. These results are published by NASA in the NASA STI Report Series, which includes the following report types:

- **TECHNICAL PUBLICATION.** Reports of completed research or a major significant phase of research that present the results of NASA programs and include extensive data or theoretical analysis. Includes compilations of significant scientific and technical data and information deemed to be of continuing reference value. NASA's counterpart of peer-reviewed formal professional papers but has less stringent limitations on manuscript length and extent of graphic presentations.
- **TECHNICAL MEMORANDUM.** Scientific and technical findings that are preliminary or of specialized interest, e.g., quick release reports, working papers, and bibliographies that contain minimal annotation. Does not contain extensive analysis.
- **CONTRACTOR REPORT.** Scientific and technical findings by NASA-sponsored contractors and grantees.

- **CONFERENCE PUBLICATION.** Collected papers from scientific and technical conferences, symposia, seminars, or other meetings sponsored or cosponsored by NASA.
- **SPECIAL PUBLICATION.** Scientific, technical, or historical information from NASA programs, projects, and missions, often concerned with subjects having substantial public interest.
- **TECHNICAL TRANSLATION.** English-language translations of foreign scientific and technical material pertinent to NASA's mission.

Specialized services that complement the STI Program Office's diverse offerings include creating custom thesauri, building customized databases, organizing and publishing research results . . . even providing videos.

For more information about the NASA STI Program Office, see the following:

- Access the NASA STI Program Home Page at <http://www.sti.nasa.gov>
- E-mail your question via the Internet to help@sti.nasa.gov
- Fax your question to the NASA Access Help Desk at 301-621-0134
- Telephone the NASA Access Help Desk at 301-621-0390
- Write to:
NASA Access Help Desk
NASA Center for Aerospace Information
7121 Standard Drive
Hanover, MD 21076



Hall Effect Thruster Interactions Data From the Russian Express-A2 and Express-A3 Satellites Acquire Express-A3 SPT-100 Based Propulsion Subsystem and Other Subsystem Flight Operation TM-Data for the Period of January 1, 2001 to and Including March 31, 2001, Task 32

N. Sitnikova, D. Volkov, I. Maximov, and V. Petrusevich
Nauchno-Proizvodstvennoe Obiedinenie Prikladnoi Mekhaniki, Krasnoyarsk region, Russia

D. Allen
Schafer Corporation, Chelmsford, Massachusetts

Prepared under Contracts NAS3-99151 and NAS3-99204

National Aeronautics and
Space Administration

Glenn Research Center

Available from

NASA Center for Aerospace Information
7121 Standard Drive
Hanover, MD 21076

Available electronically at <http://gltrs.grc.nasa.gov>

Preface

This 12-part report documents the data obtained from various sensor measurements taken aboard the Russian Express-A2 and Express-A3 spacecraft in Geosynchronous Earth Orbit (GEO). These GEO communications satellites, which were designed and built by NPO Prikladnoy Mekhaniki (NPO PM) of Zheleznogorsk, Russia, utilize Hall thruster propulsion systems for north-south and east-west station-keeping and as of June 2002, were still operating at 80° E. and 11° W., respectively. Express-A2 was launched on March 12, 2000, while Express-A3 was launched on June 24, 2000. The diagnostic equipment from which these data were taken includes electric field strength sensors, ion current and energy sensors, and pressure sensors. The diagnostics and the Hall thruster propulsion systems are described in detail along with lists of tabular data from those diagnostics and propulsion system and other satellite systems.

Space Power, Inc., now part of Pratt & Whitney's Chemical Systems Division, under contract NAS3-99151 to the NASA Glenn Research Center, obtained these data over several periods from March 12, 2000, through September 30, 2001. Each of the 12 individual reports describe, in detail, the propulsion systems as well as the diagnostic sensors utilized.

Finally, parts 11 and 12 include the requirements to which NPO PM prepared and delivered these data.

Filename	Title
CR-2003-212005-PART1.pdf	Hall Effect Thruster Interactions Data From the Russian Express-A2 and Express-A3 Satellites Acquire Express-A2 SPT-100 Based Propulsion Subsystem and Other Subsystem Flight Operation TM-Data for the Period of March 12, 2000 to and Including June 15, 2000, Task 29
CR-2003-212005-PART2.pdf	Hall Effect Thruster Interactions Data From the Russian Express-A2 and Express-A3 Satellites Acquire TM-Data for Type B Sensors for "Express-A" Number 2 Satellite for the Period of March 12, 2000 to and Including June 15, 2000, Task 25
CR-2003-212005-PART3.pdf	Hall Effect Thruster Interactions Data From the Russian Express-A2 and Express-A3 Satellites Acquire Express-A3 SPT-100 Based Propulsion Subsystem and Other Subsystem Flight Operation TM-Data for the Period of June 24, 2000 to and Including September 30, 2000, Task 30
CR-2003-212005-PART4.pdf	Hall Effect Thruster Interactions Data From the Russian Express-A2 and Express-A3 Satellites Acquire TM-Data for Type A and Type B Sensors for "Express-A" Number 3 Satellite for the Period of June 24, 2000 to and Including September 30, 2000, Task 27A

Filename	Title
CR-2003-212005-PART5.pdf	Hall Effect Thruster Interactions Data From the Russian Express-A2 and Express-A3 Satellites Acquire Express-A3 SPT-100 Based Propulsion Subsystem and Other Subsystem Flight Operation TM-Data for the Period of October 1, 2000 to and Including December 31, 2000, Task 31
CR-2003-212005-PART6.pdf	Hall Effect Thruster Interactions Data From the Russian Express-A2 and Express-A3 Satellites Acquire TM-Data for Type A and Type B Sensors for "Express-A" Number 3 Satellite for the Period of October 1, 2000 to and Including December 31, 2000, Task 27B
CR-2003-212005-PART7.pdf	Hall Effect Thruster Interactions Data From the Russian Express-A2 and Express-A3 Satellites Acquire Express-A3 SPT-100 Based Propulsion Subsystem and Other Subsystem Flight Operation TM-Data for the Period of January 1, 2001 to and Including March 31, 2001, Task 32
CR-2003-212005-PART8.pdf	Hall Effect Thruster Interactions Data From the Russian Express-A2 and Express-A3 Satellites Acquire TM-Data for Type A and Type B Sensors for "Express-A" Number 3 Satellite for the Period of January 1, 2001 to and Including March 31, 2001, Task 27C
CR-2003-212005-PART9.pdf	Hall Effect Thruster Interactions Data From the Russian Express-A2 and Express-A3 Satellites Acquire Express-A3 SPT-100 Based Propulsion Subsystem and Other Subsystem Flight Operation TM-Data for the Period of July 1, 2001 to and Including September 30, 2001, Task 33
CR-2003-212005-PART10.pdf	Hall Effect Thruster Interactions Data From the Russian Express-A2 and Express-A3 Satellites Acquire TM-Data for Type A and Type B Sensors for "Express-A" Number 3 Satellite for the Period of July 1, 2001 to and Including September 30, 2001, Task 27D
CR-2003-212005-PART11.pdf	Hall Effect Thruster Interactions Data From the Russian Express-A2 and Express-A3 Satellites Express/T-160E Project Express A2 and A3 Data Agreement Document
CR-2003-212005-PART12.pdf	Hall Effect Thruster Interactions Data From the Russian Express-A2 and Express-A3 Satellites Express/T-160E Project Express A2 and A3 Sensors Operations Procedures Document

TABLE OF CONTENTS

ABBREVIATIONS AND ACRONYMS	vi
INTRODUCTION.....	1
1. ORBIT CONTROL PROPULSION.....	2
1.1. SPT-100 THRUSTERS FUNCTIONING DATA.....	2
1.2. START-UP AND OPERATION OF THRUSTERS FOR PERFORMING STATION KEEPING OPERATIONS	5
1.2.1. Lists of Firing Commands.....	6
1.2.2. Telemetry Data Tables	7
1.3. THRUST BASED ON RANGING RESULTS DURING EAST-WEST AND NORTH-SOUTH MANEUVERS	8
1.4. COMMENTS ON SPT OPERATION	8
2. EXPRESS-A #3 ON-BOARD SUBSYSTEMS	9
2.1. POWER SUPPLY SUBSYSTEM	9
2.1.1. Temperatures of SA Panels	9
2.1.2. Parameters for SA Panels	10
2.2. ATTITUDE DETERMINATION AND CONTROL SUBSYSTEM.....	11
2.2.1. Disturbing Torques when operating the SPT-100 Thrusters during the station keeping operations (Firings #1.1 to #1.9)	11
2.2.2. Attitude Control Propulsion Subsystem.....	11
2.3. THERMAL CONTROL SUBSYSTEM	12
2.4. ON-BOARD NAVIGATION SUBSYSTEM	13
2.5. COMMUNICATIONS MODULE	13
ANNEX 1. T4C1 THRUSTER OPERATION TM-DATA BASED ON AVAILABLE TM-DATA RECEIPT SESSIONS (19/01/01)	14
ANNEX 2. RT4C2 THRUSTER OPERATION TM-DATA BASED ON AVAILABLE TM-DATA RECEIPT SESSIONS (29/01/01)	19
ANNEX 3. T4C2 THRUSTER OPERATION TM-DATA BASED ON AVAILABLE TM-DATA RECEIPT SESSIONS (30/01/01)	24
ANNEX 4. RT4C2 THRUSTER OPERATION TM-DATA BASED ON AVAILABLE TM-DATA RECEIPT SESSIONS (13/02/01)	29
ANNEX 5. T4C2 THRUSTER OPERATION TM-DATA BASED ON AVAILABLE TM-DATA RECEIPT SESSIONS (22/02/01)	34
ANNEX 6. T4C2 THRUSTER OPERATION TM-DATA BASED ON AVAILABLE TM-DATA RECEIPT SESSIONS (28/02/01)	39
ANNEX 7. T4C2 THRUSTER OPERATION TM-DATA BASED ON AVAILABLE TM-DATA RECEIPT SESSIONS (04/03/01)	44
ANNEX 8. T4C2 THRUSTER OPERATION TM-DATA BASED ON AVAILABLE TM-DATA RECEIPT SESSIONS (08/03/01)	49
ANNEX 9. RT4C2 THRUSTER OPERATION TM-DATA BASED ON AVAILABLE TM-DATA RECEIPT SESSIONS (31/03/01)	54

Abbreviations and Acronyms

A	Amps
DK	Pressure of Xenon Feed Unit output
DKR1	Pressure of primary Xenon Feed Branch
DKR2	Pressure of redundant Xenon Feed Branch
DVK	Pressure of Xenon Feed Unit input
EV	Electrical valve
EWSK	East-West Station Keeping
Hn	Heater number "n"
HETS	Hall Effect Thruster System
I	Current
NSSK	North-South Station Keeping
PRD	Pressure regulation device
PS	Propulsion System
PV	Pyrotechnic Valve
RT	Redundant Thruster
RV	Reducing Valve
SA	Solar Array
SAn	Solar Array Panel number "n"
SPT-100	Stationary Plasma Thruster with 100 mm
T	Thruster
T18R	Temperature 1 of the Cylindrical Radiator
T19R	Temperature 2 of the Cylindrical Radiator
T1PK	Temperature of Xenon Feed Unit
T1SA	Temperature of Solar Array Panel number 1
T28K	Temperature of the Pressurized Container Surface
T2SA	Temperature of Solar Array Panel number 2
TBHKn	Temperature of Xenon Storage Unit number "n"
TBK_n	Temperature of Thruster number "n"
TUn	Thruster Unit number "n"
V	Voltage, Volts
Vn	Valve number "n"
XFU	Xenon Feed Unit
XSun	Xenon Storage Unit number "n"

Introduction

The Express-A #3 Spacecraft has been entered into geostationary orbit on June 24, 2000. The spacecraft's electric jet propulsion based on the SPT-100 stationary plasma thrusters is used to provide both the longitude and inclination orbit control.

This Report is issued in accordance with the requirements of the Task #32 under the Contract #97-1088-02 and prepared in compliance with agreed upon contents of the sections of the "EXPRESS/T160E Project Express A2 and A3 Data Agreement Document dated on October 29, 2000" document.

This Document includes the flight operational data for the SPT-100 Propulsion at level of the Express-A #3 Spacecraft for a period of January 01 to March 31, 2001.

In this Document all the being measured parameters and their changes are referenced to Moscow Standard Time.

1. Orbit Control Propulsion

1.1. SPT-100 Thrusters Functioning Data

For a period of January 01 through March 31, 2001, the SPT-100 Thrusters firings were conducted to perform the longitude/inclination station keeping operations for the Express-A #3 Spacecraft.

Total operating time and number of firings for each thruster on each cathode for the period of January 01 to March 31, 2001 are provided in Table 1.

Table 1

Thruster No	Cathode No	Firing duration, hh:mm:ss	Firing number
T1	C1	00:00:00	0
T1	C2	00:00:00	0
RT1	C1	00:00:00	0
RT1	C2	00:00:00	0
T2	C1	00:00:00	0
T2	C2	00:00:00	0
RT2	C1	00:00:00	0
RT2	C2	00:00:00	0
T3	C1	00:00:00	0
T3	C2	00:00:00	0
RT3	C1	00:00:00	0
RT3	C2	00:00:00	0
T4	C1	17:59:16	11
T4	C2	33:43:08	27
RT4	C1	18:40:20	13
RT4	C2	31:51:32	25

Data for each SPT-100 firing and its duration for the reported period are provided in Table 2.

Table 2

Date (dd/mm/yy)	Thruster No	Cathode No	Operating Time (hh:mm:ss)
01/01/01	RT4	C1	02:00:00
02/01/01	RT4	C1	02:00:00
03/01/01	T4	C1	02:00:00
04/01/01	RT4	C1	02:00:00
05/01/01	RT4	C1	01:08:44
06/01/01	T4	C1	02:00:00
07/01/01	RT4	C1	01:08:44
08/01/01	RT4	C1	02:00:00
09/01/01	T4	C1	02:00:00
10/01/01	T4	C1	02:00:00
11/01/01	T4	C1	02:00:00
12/01/01	T4	C1	02:00:00
15/01/01	RT4	C1	01:11:48
16/01/01	RT4	C1	01:11:48
17/01/01	T4	C1	01:11:48
18/01/01	RT4	C1	01:11:48
19/01/01	T4	C1	01:11:52
20/01/01	RT4	C1	01:11:52
21/01/01	T4	C1	01:11:52

Date (dd/mm/yy)	Thruster No	Cathode No	Operating Time (hh:mm:ss)
22/01/01	RT4	C1	01:11:52
23/01/01	RT4	C1	01:11:52
24/01/01	T4	C1	01:11:52
25/01/01	RT4	C1	01:11:52
26/01/01	T4	C1	01:11:52
29/01/01	RT4	C2	01:11:56
30/01/01	T4	C2	01:11:56
31/01/01	T4	C2	01:11:56
01/02/01	RT4	C2	01:11:56
02/02/01	T4	C2	01:11:56
03/02/01	RT4	C2	01:11:56
04/02/01	T4	C2	01:11:56
05/02/01	RT4	C2	01:11:56
06/02/01	RT4	C2	01:12:00
07/02/01	T4	C2	01:12:00
08/02/01	T4	C2	01:12:00
09/02/01	RT4	C2	01:12:00
12/02/01	T4	C2	01:12:00
13/02/01	RT4	C2	01:12:00
14/02/01	T4	C2	01:12:04
15/02/01	RT4	C2	01:12:04
16/02/01	T4	C2	01:12:04
17/02/01	RT4	C2	01:12:04
18/02/01	T4	C2	01:12:04
19/02/01	RT4	C2	01:12:04
20/02/01	T4	C2	01:12:04
21/02/01	RT4	C2	01:12:08
22/02/01	T4	C2	01:12:08
23/02/01	RT4	C2	01:12:08
26/02/01	T4	C2	01:12:08
27/02/01	T4	C2	01:12:08
28/02/01	T4	C2	01:12:08
01/03/01	RT4	C2	01:12:12
02/03/01	T4	C2	01:12:12
03/03/01	RT4	C2	01:12:12
04/03/01	T4	C2	01:12:12
05/03/01	RT4	C2	01:12:12
06/03/01	T4	C2	01:12:12
07/03/01	RT4	C2	01:12:12
08/03/01	T4	C2	01:12:12
09/03/01	RT4	C2	01:12:16
13/03/01	RT4	C2	01:24:28
14/03/01	T4	C2	01:24:28
15/03/01	RT4	C2	01:24:32
16/03/01	T4	C2	01:24:32
17/03/01	RT4	C2	01:24:32
18/03/01	T4	C2	01:24:32
19/03/01	RT4	C2	01:24:32
20/03/01	T4	C2	01:24:32
21/03/01	RT4	C2	01:24:32
22/03/01	T4	C2	01:24:32
23/03/01	T4	C2	00:02:04

Date (dd/mm/yy)	Thruster No	Cathode No	Operating Time (hh:mm:ss)
27/03/01	RT4	C2	01:24:32
28/03/01	T4	C2	01:24:32
29/03/01	RT4	C2	01:24:32
30/03/01	T4	C2	01:24:36
31/03/01	RT4	C2	01:24:36

1.2. Start-up and operation of thrusters for performing station keeping operations

SPT-100 Thruster Flight Operation Data when performing the station keeping operations is provided for the following firings:

# 1.1)	Thruster:	T4C1
	Date and Time of switching on:	19/01/01 at 13:52:44;
	Date and Time of switching off:	19/01/01 at 15:04:36.
	Operating Time:	01:11:52.
# 1.2)	Thruster:	RT4C2
	Date and Time of switching on:	29/01/01 at 13:13:17;
	Date and Time of switching off:	29/01/01 at 14:25:11.
	Operating Time:	01:11:56.
# 1.3)	Thruster:	T4C2
	Date and Time of switching on:	30/01/01 at 13:09:25;
	Date and Time of switching off:	30/01/01 at 14:21:21.
	Operating Time:	01:11:56.
# 1.4)	Thruster:	RT4C2
	Date and Time of switching on:	13/02/01 at 12:14:28;
	Date and Time of switching off:	13/02/01 at 13:26:28.
	Operating Time:	01:12:00.
# 1.5)	Thruster:	T4C2
	Date and Time of switching on:	22/02/01 at 11:39:01;
	Date and Time of switching off:	22/02/01 at 12:51:09.
	Operating Time:	01:12:08.
# 1.6)	Thruster:	T4C2
	Date and Time of switching on:	28/02/01 at 11:15:17;
	Date and Time of switching off:	28/02/01 at 12:27:25.
	Operating Time:	01:12:08.
# 1.7)	Thruster:	T4C2
	Date and Time of switching on:	04/03/01 at 10:59:24;
	Date and Time of switching off:	04/03/01 at 12:11:36.
	Operating Time:	01:12:12.
# 1.8)	Thruster:	T4C2
	Date and Time of switching on:	08/03/01 at 10:43:33;
	Date and Time of switching off:	08/03/01 at 11:55:45.
	Operating Time:	01:12:12.
# 1.9)	Thruster:	RT4C2
	Date and Time of switching on:	31/03/01 at 09:06:53;
	Date and Time of switching off:	31/01/01 at 10:31:29.
	Operating Time:	01:24:36.

1.2.1. Lists of Firing Commands

Sequence of commands for firing the thrusters #1.1 to #1.6 and date and time of their execution are provided in Table 3. Sequence of commands for firing the thrusters #1.7 to #1.9 and date and time of their execution are provided in Table 4.

Table 3

Command	Date and Time of Execution				
	# 1.1 19/01/01	# 1.2 29/01/01	# 1.3 30/01/01	# 1.4 13/02/01	# 1.5 22/02/01
Channel "minus Z"	13:48:04	13:08:32	13:04:36	12:09:48	11:34:21
RV1 Opening	13:48:04	13:08:32	13:04:36	12:09:48	11:34:21
T(RT) Preparation	13:50:04	13:10:32	13:06:36	12:11:48	11:36:21
C1 (C2) Preparation	13:50:06	13:10:35	13:06:38	12:11:50	11:36:23
Opening T Valves	13:52:36	13:13:05	13:09:08	12:14:20	11:38:53
Ignition	13:52:44	13:13:13	13:09:16	12:14:28	11:39:01
C Switching Off	13:52:44	13:13:19	13:09:25	12:14:28	11:39:01
RV Closing	14:54:36	14:15:13	14:11:21	13:16:28	12:41:09
T Switching Off	15:04:36	14:25:13	14:21:21	13:26:28	12:51:09

Note:

1. When Firing 1.2 a time period between the "IGNITION" command and the thruster start-up (when a charge current is appeared) is 4 sec.
2. When Firing 1.3 a time period between the "IGNITION" command and the thruster start-up (when a charge current is appeared) is 8 sec.

Table 4

Command	Date and Time of Execution			
	# 1.6 28/02/01	# 1.7 04/03/01	# 1.8 08/03/01	# 1.9 31/03/01
Channel "minus Z"	11:10:36	10:54:44	10:38:53	09:02:13
RV1 Opening	11:10:36	10:54:44	10:38:53	09:02:13
T (RT) Preparation	11:12:36	10:56:45	10:40:53	09:04:13
C2 Preparation	11:12:38	10:56:46	10:40:55	09:04:15
T Valves Opening	11:15:08	10:59:16	10:43:25	09:06:45
Ignition	11:15:16	10:59:24	10:43:33	09:06:53
C Switching Off	11:15:17	10:59:25	10:43:33	09:06:53
RV Closing	12:17:25	12:01:36	11:45:45	10:21:29
T Switching Off	12:27:25	12:11:36	11:55:45	10:31:29

1.2.2. Telemetry Data Tables

- #1.1) Telemetry data table when operating the T4C1 Thruster on 19/01/01 is given in Annex 1.
- #1.2) Telemetry data table when operating the RT4C2 Thruster on 29/01/01 is given in Annex 2.
- #1.3) Telemetry data table when operating the T4C2 Thruster on 30/01/01 is given in Annex 3.
- #1.4) Telemetry data table when operating the RT4C2 Thruster on 13/02/01 is given in Annex 4.
- #1.5) Telemetry data table when operating the T4C2 Thruster on 22/02/01 is given in Annex 5.
- #1.6) Telemetry data table when operating the T4C2 Thruster on 28/02/01 is given in Annex 6.
- #1.7) Telemetry data table when operating the T4C2 Thruster on 04/03/01 is given in Annex 7.
- #1.8) Telemetry data table when operating the T4C2 Thruster on 08/03/01 is given in Annex 8.
- #1.9) Telemetry data table when operating the RT4C2 Thruster on 31/03/01 is given in Annex 9.

1.3. Thrust based on ranging results during East-West and North-South maneuvers

Effective thrust determination results for Express-A #3 Orbit Control Propulsion Subsystem are given in Table 5.

Table 5

Thruster Operating Period	Thruster No	Effective Thrust, mN
27.12 – 12.01.2001	T4, RT4 (C1)	70,5
15 – 26.01.2001	T4, RT4 (C1)	77,1
29.01 – 9.02.2001	T4, RT4 (C2)	69,0
12 – 23.02.2001	T4, RT4 (C2)	68,0
26.02 – 9.03.2001	T4, RT4 (C2)	71,1
13 – 22.03.2001	T4, RT4 (C2)	79,5
27.03 – 6.04.2001	T4, RT4 (C2)	82,5

For the North-South orbit control thrusters T4 and RT4 when determining a mean-integral value of effective thrust it was assumed that thrust values of all thrusters at all firings to be fell in a measurement interval are equal. In this case the measurement interval is a time period between two ranging cycles, of which there are performed SPT-100 thruster firings.

The longer the measurement interval, the higher an accuracy of mean-integral thrust value calculation. This is clarified as follows: the longer the measurement interval, the greater the change of orbit parameters due to the SPT-100 thruster firings, and accordingly, the lesser an influence of possible uncertainties when determining the orbit parameters based on the ranging data.

1.4. Comments on SPT Operation

No any comments on SPT-100 operation within the period of 01/01/01 to 31/03/01 are recorded. All the operations on the Express-A #3 Orbit Control Propulsion Subsystem were performed in accordance with the specified logic and no any additional measures were taken.

2. Express-A #3 On-Board Subsystems

2.1. Power Supply Subsystem

2.1.1. Temperatures of SA Panels

Table 6 provides the SA temperature variations for a day of 20/03/01.

Table 6

Time	SA Panel 1 Temperature (°C)	SA Panel 2 Temperature (°C)
00:00:00	43,9	41,7
01:00:00	45,1	41,7
02:00:00	43,9	40,6
03:00:00	43,9	40,6
04:00:00	43,9	41,7
05:00:00	45,1	40,6
06:00:00	45,1	41,7
07:00:00	45,1	41,7
08:00:00	45,1	42,8
09:00:00	45,1	40,6
10:00:00	45,1	41,7
11:00:00	45,1	40,6
12:00:00	45,1	41,7
13:00:00	46,2	41,7
14:00:00	45,1	41,7
15:00:00	43,9	40,6
16:00:00	43,9	40,6
17:00:00	43,9	42,8
18:00:00	45,1	43,9
19:00:00	45,1	42,8
20:00:00	43,9	41,7
21:00:00	43,9	41,7
22:00:00	41,7	38,3
23:00:00	41,7	40,6
00:00:00	43,9	42,8

2.1.2. Parameters for SA Panels

Table 7 provides information on parameters for the SA panels. They were measured once per month during a flight operation of the Express-A #3 satellite.

Table 7

Date & Time of Measurement	Panels SA1 & SA2		Panel SA3		Panel SA4	
	I _{CC} (A)	U _{OC} (V)	I _{CC} (A)	U _{OC} (V)	I _{CC} (A)	U _{OC} (V)
19/01/01 13:50	101,1	46,1	17,2	45,5	17,2	45,5
22/02/01 11:20	104,9	45,5	17,9	44,8	17,9	44,8
21/03/00 11:15	105,0	46,3	17,9	45,2	17,9	45,2

Notes:

1. I_{CC} is SA output current.
2. U_{OC} is open-circuit voltage.
3. Output currents for the SA1 and SA2 sections are measured at voltage of 30,3 V; for the SA3 and SA4 sections - at 27,8 V.
4. Steps of measurement are:
 - Current of SA1 and SA2 Sections are: 0,7 A,
 - Current of SA3 and SA4 Sections are: 0,2 A,
 - Voltage: 0.3 V.

2.2. Attitude Determination and Control Subsystem

2.2.1. Disturbing Torques when operating the SPT-100 Thrusters during the station keeping operations (Firings #1.1 to #1.9)

Values of the disturbing torques (M_x , M_y , M_z) observable when operating the SPT-100 thrusters are provided in Table 8.

Table 8

Thruster #	Cathode #	SA Angle (degrees)	Data (dd/mm/yy)	Disturbing Torque X (N·m)	Disturbing Torque Y (N·m)	Disturbing Torque Z (N·m)
T4	C1	60	19.01.2001	1.01E-03	-3.67E-03	1.18E-05
		75		8.99E-05	-4.25E-03	-1.30E-04
RT4	C2	60	29.01.2001	1.97E-03	-2.87E-03	1.96E-04
T4	C2	45	30.01.2001	1.57E-03	-2.73E-03	3.12E-04
RT4	C2	45	13.02.2001	2.46E-03	-1.85E-03	1.60E-04
T4	C2	30	22.02.2001	1.78E-03	-8.66E-04	2.22E-04
T4	C2	30	28.02.2001	1.77E-03	-7.74E-04	2.40E-04
T4	C2	15	04.03.2001	1.12E-03	1.81E-03	3.49E-04
		30		1.74E-03	-7.02E-04	2.23E-04
T4	C2	15	08.03.2001	8.90E-04	1.62E-03	3.21E-04
		30		1.72E-03	-7.26E-04	2.23E-04
RT4	C2	0	31.03.2001	-5.57E-04	2.64E-03	-3.67E-04

2.2.2. Attitude Control Propulsion Subsystem

A propellant flow rate for the Express-A #3 Attitude Control Propulsion Subsystem in order to compensate the disturbing torques at the firings #1.1 through #1.9 is given in Table 9.

Table 9

Firing No	Thruster No	Propellant Flow Rate (grams)
1.1	T4C1	≈ 2,3
1.2	RT4C2	≈ 4,9
1.3	T4C2	≈ 3,6
1.4	RT4C2	≈ 6,9
1.5	T4C2	≈ 1,0
1.6	T4C2	≈ 3,8
1.7	T4C2	≈ 0,9
1.8	T4C2	≈ 1,8
1.9	RT4C2	≈ 0,8

2.3. Thermal Control Subsystem

Table 10 provides daily temperature change data (Parameters T18R and T19R) for the Radiator as well as for a surface of the Pressurized Container (T28K). The parameters were measured on March 21, 2001 with an interval of 60 min.

Table 10

Time (hh:mm:ss)	Cylindrical Radiator Temperature 1 (°C)	Cylindrical Radiator Temperature 2 (°C)	Pressurized Container Surface Temperature (°C)
00:00:01	-2,92	-13,89	17,03
01:00:01	-4,61	-15,58	16,7
02:00:01	-7,98	-18,11	16,04
03:00:01	-20,64	-26,54	14,72
04:00:00	-29,92	-35,82	14,06
05:00:01	-29,07	-29,07	14,06
06:00:01	-23,17	-18,95	13,73
07:00:01	-18,11	-11,36	14,39
08:00:01	-14,73	-7,14	14,39
09:00:00	-12,2	-4,61	14,72
10:00:01	-12,2	-2,08	15,38
11:00:01	-7,98	2,14	16,04
12:00:00	-4,61	2,98	16,04
13:00:00	-3,77	2,14	16,04
14:00:00	-3,77	-0,39	15,71
15:00:00	-7,14	-7,14	15,38
16:00:00	-11,36	-16,42	14,72
17:00:00	-9,67	-17,26	14,39
18:00:00	-4,61	-14,73	14,72
19:00:01	-0,39	-11,36	15,71
20:00:01	1,29	-8,83	16,37
21:00:01	1,29	-9,67	16,7
22:00:01	0,45	-11,36	17,03
23:00:01	-1,24	-12,2	17,03

2.4. On-Board Navigation Subsystem

Express-A #3 orbit parameters on the date of ranging session are provided in Table 11 below.

Table 11

Date of Ranging Session	Time (Moscow Standard Time)	Greenwich Longitude	Inclination
13.01.2001	20:12:44	11.06.11 W	00.02.24,9
27.01.2001	19:17:23	11.01.27 W	00.01.59,0
10.02.2001	18:22:17	11.00.38 W	00.01.36,0
24.02.2001	17:27:20	11.01.50 W	00.01.51,0
10.03.2001	16:32:10	11.00.14 W	00.02.07,4
24.03.2001	15:37:08	11.00.19 W	00.03.14,9

2.5. Communications Module

Within a period of 01/01/01 to 31/03/01 when firing the SPT-100 Thrusters no any facts of anomalous telemetry data receipt were registered.

Within a period of 01/01/01 to 31/03/01 when firing the SPT-100 thrusters, an influence of propulsion on the communications module transponders operation performance was not recorded.

Annex 1. T4C1 Thruster Operation TM-data based on available TM-data receipt sessions (19/01/01)

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
13:47:54	0,00	0,00	0,00	2,84	
13:48:04	0,00	0,00	0,00	2,84	
13:48:14	0,00	0,00	0,00	2,84	
13:48:24	0,00	0,00	0,00	2,84	
13:48:34	0,00	0,00	0,00	2,84	
13:48:44	0,00	0,00	0,00	2,84	
13:48:54	0,00	0,00	0,00	2,84	
13:49:04	0,00	0,00	0,00	2,84	
13:49:14	0,00	0,00	0,00	2,84	
13:49:24	0,00	0,00	0,00	2,84	
13:49:34	0,00	0,00	0,00	2,84	
13:49:44	0,00	0,00	0,00	2,84	
13:49:54	0,00	0,00	0,00	2,84	
13:50:04	0,00	0,00	346	2,84	
13:50:14	11,80	0,00	326	2,84	
13:50:24	11,80	0,00	326	2,84	
13:50:34	11,90	0,00	326	2,84	
13:50:44	12,00	0,00	326	2,84	
13:50:54	12,00	0,00	326	2,84	
13:51:04	12,00	0,00	326	2,84	
13:51:14	12,10	0,00	326	2,84	
13:51:24	11,90	0,00	326	2,84	
13:51:34	12,00	0,00	326	2,84	
13:51:44	12,10	0,00	326	2,84	
13:51:54	12,00	0,00	326	2,84	
13:52:04	12,00	0,00	326	2,84	
13:52:14	12,00	0,00	326	2,84	
13:52:24	11,90	0,00	326	2,84	
13:52:34	12,10	0,00	326	2,84	
13:52:44	12,20	0,00	326	2,84	
13:52:54	0,00	3,61	318	2,81	
13:53:04	0,00	4,59	314	2,81	
13:53:14	0,00	4,62	305	2,78	
13:53:44	0,00	4,62	310	2,75	
13:54:14	0,00	4,68	308	2,72	
13:54:44	0,00	4,71	308	2,66	
13:55:14	0,00	4,77	308	2,63	
13:55:44	0,00	4,65	310	2,60	
13:56:14	0,00	4,74	310	2,84	
13:56:44	0,00	4,62	310	2,78	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
13:57:14	0,00	4,65	314	2,75	
13:57:44	0,00	4,62	310	2,72	
13:58:14	0,00	4,65	310	2,66	
13:58:44	0,00	4,65	314	2,63	
13:59:14	0,00	4,68	308	2,69	
13:59:44	0,00	4,65	310	2,84	
14:00:14	0,00	4,65	314	2,78	
14:00:44	0,00	4,65	312	2,75	
14:01:14	0,00	4,62	318	2,72	
14:01:44	0,00	4,68	314	2,66	
14:02:14	0,00	4,62	310	2,60	
14:02:44	0,00	4,74	308	2,84	
14:03:14	0,00	4,77	310	2,78	
14:03:44	0,00	4,65	314	2,75	
14:04:14	0,00	4,77	310	2,69	
14:04:44	0,00	4,65	308	2,69	
14:05:14	0,00	4,77	308	2,63	
14:05:44	0,00	4,68	310	2,78	
14:06:14	0,00	4,65	308	2,81	
14:06:44	0,00	4,62	318	2,75	
14:07:14	0,00	4,62	316	2,72	
14:07:44	0,00	4,62	318	2,66	
14:08:14	0,00	4,87	310	2,63	
14:08:44	0,00	4,71	308	2,75	
14:09:14	0,00	4,74	308	2,84	
14:09:44	0,00	4,65	308	2,75	
14:10:14	0,00	4,65	318	2,72	
14:10:44	0,00	4,65	316	2,66	
14:11:14	0,00	4,68	308	2,63	
14:11:44	0,00	4,65	318	2,69	
14:12:14	0,00	4,65	308	2,87	
14:12:44	0,00	4,65	318	2,78	
14:13:14	0,00	4,65	310	2,72	
14:13:44	0,00	4,65	310	2,66	
14:14:14	0,00	4,62	310	2,63	
14:14:44	0,00	4,71	308	2,63	
14:15:14	0,00	4,65	308	2,84	
14:15:44	0,00	4,65	308	2,78	
14:16:14	0,00	4,62	308	2,72	
14:16:44	0,00	4,87	308	2,72	
14:17:14	0,00	4,65	314	2,66	
14:17:44	0,00	4,65	318	2,60	
14:18:14	0,00	4,62	310	2,84	
14:18:44	0,00	4,65	308	2,78	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
14:19:14	0,00	4,77	308	2,75	
14:19:44	0,00	4,87	308	2,72	
14:20:14	0,00	4,65	308	2,66	
14:20:44	0,00	4,77	308	2,63	
14:21:14	0,00	4,65	314	2,78	
14:21:44	0,00	4,65	308	2,81	
14:22:14	0,00	4,65	308	2,75	
14:22:44	0,00	4,65	316	2,72	
14:23:14	0,00	4,77	308	2,66	
14:23:44	0,00	4,62	310	2,63	
14:24:14	0,00	4,62	308	2,75	
14:24:44	0,00	4,65	316	2,81	
14:25:14	0,00	4,68	308	2,75	
14:25:44	0,00	4,77	308	2,72	
14:26:14	0,00	4,62	316	2,66	
14:26:44	0,00	4,68	308	2,63	
14:27:14	0,00	4,71	308	2,69	
14:27:44	0,00	4,74	308	2,84	
14:28:14	0,00	4,77	308	2,78	
14:28:44	0,00	4,68	308	2,72	
14:29:14	0,00	4,77	308	2,69	
14:29:44	0,00	4,68	310	2,66	
14:30:14	0,00	4,62	314	2,63	
14:30:44	0,00	4,62	308	2,84	
14:31:14	0,00	4,62	310	2,78	
14:31:44	0,00	4,65	310	2,75	
14:32:14	0,00	4,74	308	2,72	
14:32:44	0,00	4,65	316	2,66	
14:33:14	0,00	4,62	308	2,60	
14:33:44	0,00	4,65	310	2,87	
14:34:14	0,00	4,74	308	2,81	
14:34:44	0,00	4,62	308	2,75	
14:35:14	0,00	4,71	310	2,72	
14:35:44	0,00	4,59	314	2,69	
14:36:14	0,00	4,65	310	2,63	
14:36:44	0,00	4,77	308	2,75	
14:37:14	0,00	4,62	308	2,84	
14:37:44	0,00	4,74	308	2,75	
14:38:14	0,00	4,87	308	2,72	
14:38:44	0,00	4,77	305	2,66	
14:39:14	0,00	4,65	310	2,63	
14:39:44	0,00	4,65	308	2,72	
14:40:14	0,00	4,74	308	2,84	
14:40:44	0,00	4,77	308	2,78	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
14:41:14	0,00	4,62	314	2,72	
14:41:44	0,00	4,62	308	2,69	
14:42:14	0,00	4,62	314	2,66	
14:42:44	0,00	4,62	308	2,66	
14:43:14	0,00	4,62	310	2,84	
14:43:44	0,00	4,77	308	2,78	
14:44:14	0,00	4,71	308	2,72	
14:44:44	0,00	4,68	308	2,72	
14:45:14	0,00	4,74	308	2,66	
14:45:44	0,00	4,62	310	2,60	
14:46:14	0,00	4,65	308	2,84	
14:46:44	0,00	4,74	308	2,78	
14:47:14	0,00	4,65	308	2,75	
14:47:44	0,00	4,62	310	2,72	
14:48:14	0,00	4,74	310	2,66	
14:48:44	0,00	4,65	326	2,63	
14:49:14	0,00	4,65	308	2,84	
14:49:44	0,00	4,65	310	2,78	
14:50:14	0,00	4,71	308	2,75	
14:50:44	0,00	4,62	305	2,72	
14:51:14	0,00	4,65	308	2,66	
14:51:44	0,00	4,62	310	2,63	
14:52:14	0,00	4,74	308	2,72	
14:52:44	0,00	4,71	308	2,84	
14:53:14	0,00	4,65	318	2,75	
14:53:44	0,00	4,65	316	2,72	
14:54:14	0,00	4,65	310	2,66	
14:54:44	0,00	4,65	310	2,63	
14:55:14	0,00	4,62	326	2,66	
14:55:44	0,00	4,74	308	2,84	
14:56:14	0,00	4,71	308	2,78	
14:56:44	0,00	4,65	310	2,75	
14:57:14	0,00	4,65	308	2,72	
14:57:44	0,00	4,65	308	2,63	
14:58:14	0,00	4,77	308	2,60	
14:58:44	0,00	4,65	310	2,84	
14:59:14	0,00	4,65	310	2,81	
14:59:44	0,00	4,71	308	2,75	
15:00:14	0,00	4,74	308	2,72	
15:00:44	0,00	4,65	314	2,66	
15:01:14	0,00	4,65	334	2,63	
15:01:44	0,00	4,62	308	2,60	
15:02:14	0,00	4,65	308	2,84	
15:02:44	0,00	4,77	308	2,81	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
15:03:14	0,00	4,77	308	2,75	
15:03:44	0,00	4,62	310	2,72	
15:04:14	0,00	4,65	316	2,66	
15:04:44	0,00	0,00	0,00	2,63	
15:05:14	0,00	0,00	0,00	2,63	
15:05:44	0,00	0,00	0,00	2,63	

Time hh:mm:ss	Xe Feed Unit Input	Primary Xe Feed Branch	Redundant Xe Feed Branch	Xe Storage Unit 1	Xe Storage Unit 2	Xe Storage Unit 3	Xe Feed Unit	Thruster Unit 4
	Pressure (kgf/cm ²)			Temperature (°C)				
13:50:12	61,63	4,88	4,02	13,77	12,20	14,82	16,34	18,01
14:27:59	61,63	4,88	4,02	13,77	12,20	14,82	16,34	21,34
14:54:51	61,63	4,81	4,02	13,77	12,20	14,82	16,34	21,34
14:58:43	61,63	4,74	4,02	13,77	12,20	14,82	16,34	21,34
15:02:01	61,63	4,67	4,02	13,77	12,20	14,82	16,34	21,34

Annex 2. RT4C2 Thruster Operation TM-data based on available TM-data receipt sessions (29/01/01)

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
13:08:07	0,00	0,00	0,00	2,84	
13:08:17	0,00	0,00	0,00	2,84	
13:08:27	0,00	0,00	0,00	2,84	
13:08:37	0,00	0,00	0,00	2,84	
13:08:47	0,00	0,00	0,00	2,84	
13:08:57	0,00	0,00	0,00	2,84	
13:09:07	0,00	0,00	0,00	2,84	
13:09:17	0,00	0,00	0,00	2,84	
13:09:27	0,00	0,00	0,00	2,84	
13:09:37	0,00	0,00	0,00	2,84	
13:09:47	0,00	0,00	0,00	2,84	
13:09:57	0,00	0,00	0,00	2,84	
13:10:07	0,00	0,00	0,00	2,84	
13:10:17	0,00	0,00	0,00	2,84	
13:10:27	0,00	0,00	0,00	2,84	
13:10:37	12,00	0,00	322	2,84	
13:10:47	12,00	0,00	322	2,84	
13:10:57	12,00	0,00	322	2,84	
13:11:07	12,00	0,00	322	2,84	
13:11:17	12,20	0,00	322	2,84	
13:11:27	12,10	0,00	322	2,84	
13:11:37	12,00	0,00	322	2,84	
13:11:47	12,00	0,00	322	2,84	
13:11:57	11,90	0,00	322	2,84	
13:12:07	11,90	0,00	322	2,84	
13:12:17	12,00	0,00	322	2,84	
13:12:27	12,00	0,00	322	2,84	
13:12:37	12,00	0,00	322	2,84	
13:12:47	12,00	0,00	322	2,84	
13:12:57	12,00	0,00	322	2,84	
13:13:07	12,00	0,00	322	2,81	
13:13:17	12,20	0,00	318	2,78	A time period between the "IGNITION" command and the thruster start-up (when a charge current is appeared) is 4 sec.
13:13:27	0,00	3,92	308	2,78	
13:13:47	0,00	4,65	308	2,75	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
13:14:17	0,00	4,62	308	2,72	
13:14:47	0,00	4,62	318	2,66	
13:15:17	0,00	4,65	305	2,63	
13:15:47	0,00	4,62	308	2,84	
13:16:17	0,00	4,62	305	2,78	
13:16:47	0,00	4,62	308	2,75	
13:17:17	0,00	4,62	308	2,72	
13:17:47	0,00	4,65	314	2,66	
13:18:17	0,00	4,68	305	2,63	
13:18:47	0,00	4,62	305	2,72	
13:19:17	0,00	4,56	308	2,84	
13:19:47	0,00	4,62	308	2,78	
13:20:17	0,00	4,68	310	2,72	
13:20:47	0,00	4,65	310	2,66	
13:21:17	0,00	4,62	308	2,63	
13:21:47	0,00	4,71	308	2,69	
13:22:17	0,00	4,68	308	2,84	
13:22:47	0,00	4,68	308	2,78	
13:23:17	0,00	4,62	308	2,72	
13:23:47	0,00	4,62	310	2,69	
13:24:17	0,00	4,62	305	2,63	
13:24:47	0,00	4,68	308	2,69	
13:25:17	0,00	4,62	308	2,84	
13:25:47	0,00	4,62	308	2,78	
13:26:17	0,00	4,65	308	2,72	
13:26:47	0,00	4,59	305	2,69	
13:27:17	0,00	4,62	308	2,63	
13:27:47	0,00	4,62	308	2,66	
13:28:17	0,00	4,65	308	2,84	
13:28:47	0,00	4,65	305	2,78	
13:29:17	0,00	4,62	308	2,75	
13:29:47	0,00	4,65	318	2,72	
13:30:17	0,00	4,62	308	2,66	
13:30:47	0,00	4,65	308	2,63	
13:31:17	0,00	4,77	308	2,75	
13:31:47	0,00	4,62	305	2,84	
13:32:17	0,00	4,59	310	2,78	
13:32:47	0,00	4,59	308	2,72	
13:33:17	0,00	4,65	308	2,69	
13:33:47	0,00	4,65	305	2,63	
13:34:17	0,00	4,62	310	2,57	
13:34:47	0,00	4,62	308	2,84	
13:35:17	0,00	4,62	308	2,81	
13:35:47	0,00	4,65	310	2,75	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
13:36:17	0,00	4,65	308	2,69	
13:36:47	0,00	4,62	310	2,66	
13:37:17	0,00	4,68	310	2,63	
13:37:47	0,00	4,62	305	2,78	
13:38:17	0,00	4,62	308	2,84	
13:38:47	0,00	4,65	310	2,78	
13:39:17	0,00	4,62	308	2,72	
13:39:47	0,00	4,62	308	2,66	
13:40:17	0,00	4,65	308	2,66	
13:40:47	0,00	4,62	305	2,57	
13:41:17	0,00	4,59	308	2,81	
13:41:47	0,00	4,65	308	2,81	
13:42:17	0,00	4,71	308	2,75	
13:42:47	0,00	4,62	308	2,72	
13:43:17	0,00	4,62	308	2,66	
13:43:47	0,00	4,62	308	2,63	
13:44:17	0,00	4,62	310	2,81	
13:44:47	0,00	4,65	308	2,84	
13:45:17	0,00	4,62	314	2,75	
13:45:47	0,00	4,68	310	2,72	
13:46:17	0,00	4,62	308	2,66	
13:46:47	0,00	4,68	310	2,63	
13:47:17	0,00	4,71	308	2,57	
13:47:47	0,00	4,65	308	2,84	
13:48:17	0,00	4,62	308	2,81	
13:48:47	0,00	4,62	308	2,75	
13:49:17	0,00	4,71	308	2,69	
13:49:47	0,00	4,62	308	2,66	
13:50:17	0,00	4,77	308	2,63	
13:50:47	0,00	4,68	310	2,81	
13:51:17	0,00	4,62	314	2,84	
13:51:47	0,00	4,77	308	2,75	
13:52:17	0,00	4,74	308	2,72	
13:52:47	0,00	4,65	308	2,66	
13:53:17	0,00	4,65	308	2,63	
13:53:47	0,00	4,62	308	2,57	
13:54:17	0,00	4,77	308	2,81	
13:54:47	0,00	4,65	314	2,81	
13:55:17	0,00	4,62	308	2,75	
13:55:47	0,00	4,62	310	2,72	
13:56:17	0,00	4,62	308	2,63	
13:56:47	0,00	4,65	310	2,60	
13:57:17	0,00	4,59	305	2,57	
13:57:47	0,00	4,65	305	2,84	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
13:58:17	0,00	4,74	310	2,81	
13:58:47	0,00	4,65	314	2,75	
13:59:17	0,00	4,62	308	2,72	
13:59:47	0,00	4,62	308	2,66	
14:00:17	0,00	4,65	308	2,63	
14:00:47	0,00	4,74	308	2,63	
14:01:17	0,00	4,59	308	2,84	
14:01:47	0,00	4,68	310	2,78	
14:02:17	0,00	4,65	308	2,75	
14:02:47	0,00	4,62	308	2,72	
14:03:17	0,00	4,62	308	2,66	
14:03:47	0,00	4,62	308	2,63	
14:04:17	0,00	4,62	305	2,63	
14:04:47	0,00	4,65	318	2,84	
14:05:17	0,00	4,62	308	2,78	
14:05:47	0,00	4,65	308	2,75	
14:06:17	0,00	4,62	308	2,72	
14:06:47	0,00	4,62	308	2,66	
14:07:17	0,00	4,59	308	2,63	
14:07:47	0,00	4,65	305	2,69	
14:08:17	0,00	4,74	308	2,84	
14:08:47	0,00	4,71	308	2,78	
14:09:17	0,00	4,62	310	2,75	
14:09:47	0,00	4,65	308	2,72	
14:10:17	0,00	4,62	305	2,66	
14:10:47	0,00	4,62	308	2,63	
14:11:17	0,00	4,65	308	2,75	
14:11:47	0,00	4,65	308	2,84	
14:12:17	0,00	4,59	308	2,78	
14:12:47	0,00	4,62	308	2,72	
14:13:17	0,00	4,77	308	2,72	
14:13:47	0,00	4,65	308	2,66	
14:14:17	0,00	4,62	308	2,57	
14:14:47	0,00	4,65	310	2,84	
14:15:17	0,00	4,62	310	2,78	
14:15:47	0,00	4,62	305	2,75	
14:16:17	0,00	4,71	308	2,69	
14:16:47	0,00	4,62	308	2,66	
14:17:17	0,00	4,62	308	2,66	
14:17:47	0,00	4,68	308	2,63	
14:18:17	0,00	4,62	310	2,84	
14:18:47	0,00	4,65	308	2,78	
14:19:17	0,00	4,65	310	2,75	
14:19:47	0,00	4,62	305	2,72	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
14:20:17	0,00	4,59	310	2,69	
14:20:47	0,00	4,62	308	2,63	
14:21:17	0,00	4,68	305	2,66	
14:21:47	0,00	4,65	318	2,84	
14:22:17	0,00	4,65	308	2,78	
14:22:47	0,00	4,68	310	2,75	
14:23:17	0,00	4,62	308	2,72	
14:23:47	0,00	4,62	308	2,66	
14:24:17	0,00	4,62	305	2,63	
14:24:47	0,00	4,65	308	2,66	
14:25:17	0,00	0,00	0,00	2,84	
14:25:47	0,00	0,00	0,00	2,84	
14:26:17	0,00	0,00	0,00	2,84	

Time hh:mm:ss	Xe Feed Unit Input	Primary Xe Feed Branch	Redundant Xe Feed Branch	Xe Storage Unit 1	Xe Storage Unit 2	Xe Storage Unit 3	Xe Feed Unit	Thruster Unit 4
	Pressure (kgf/cm ²)			Temperature (°C)				
13:10:04	59,00	4,95	4,09	13,25	11,68	14,29	16,86	16,01
13:49:19	59,00	4,95	4,09	13,25	11,68	14,29	16,86	19,34
14:17:45	59,00	4,81	4,09	13,25	11,68	14,29	16,86	19,34
14:21:33	59,00	4,67	4,09	13,25	11,68	14,29	16,86	19,34
14:23:42	59,00	4,67	4,09	13,25	11,68	14,29	16,86	22,67
14:24:19	59,00	4,59	4,09	13,25	11,68	14,29	16,86	22,67

Annex 3. T4C2 Thruster Operation TM-data based on available TM-data receipt sessions (30/01/01)

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
13:04:05	0,00	0,00	0,00	2,84	
13:04:15	0,00	0,00	0,00	2,84	
13:04:25	0,00	0,00	0,00	2,84	
13:04:35	0,00	0,00	0,00	2,84	
13:04:45	0,00	0,00	0,00	2,84	
13:04:55	0,00	0,00	0,00	2,84	
13:05:05	0,00	0,00	0,00	2,84	
13:05:15	0,00	0,00	0,00	2,84	
13:05:25	0,00	0,00	0,00	2,84	
13:05:35	0,00	0,00	0,00	2,84	
13:05:45	0,00	0,00	0,00	2,84	
13:05:55	0,00	0,00	0,00	2,84	
13:06:05	0,00	0,00	0,00	2,84	
13:06:15	0,00	0,00	0,00	2,84	
13:06:25	0,00	0,00	0,00	2,84	
13:06:35	0,00	0,00	0,00	2,84	
13:06:45	12,00	0,00	326	2,84	
13:06:55	12,00	0,00	326	2,84	
13:07:05	12,00	0,00	326	2,84	
13:07:15	12,10	0,00	326	2,84	
13:07:25	12,10	0,00	326	2,84	
13:07:35	12,00	0,00	326	2,84	
13:07:45	12,00	0,00	326	2,84	
13:07:55	11,90	0,00	326	2,84	
13:08:05	12,20	0,00	326	2,84	
13:08:15	12,10	0,00	326	2,84	
13:08:25	12,10	0,00	326	2,84	
13:08:35	12,00	0,00	326	2,84	
13:08:45	12,00	0,00	326	2,84	
13:08:55	12,10	0,00	326	2,84	
13:09:05	12,00	0,00	326	2,84	
13:09:15	12,00	0,00	326	2,84	
13:09:25	0,00	3,73	310	2,78	A time period between the “IGNITION” command and the thruster start-up (when a charge current is appeared) is 8 sec.
13:09:35	0,00	4,62	310	2,78	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
13:09:55	0,00	4,65	316	2,72	
13:10:25	0,00	4,62	308	2,72	
13:10:55	0,00	4,62	310	2,63	
13:11:25	0,00	4,65	308	2,66	
13:11:55	0,00	4,65	316	2,81	
13:12:25	0,00	4,65	310	2,75	
13:12:55	0,00	4,65	308	2,72	
13:13:25	0,00	4,68	316	2,66	
13:13:55	0,00	4,65	316	2,63	
13:14:25	0,00	4,65	310	2,60	
13:14:55	0,00	4,74	310	2,72	
13:15:25	0,00	4,65	308	2,84	
13:15:55	0,00	4,65	318	2,78	
13:16:25	0,00	4,62	310	2,72	
13:16:55	0,00	4,62	318	2,66	
13:17:25	0,00	4,65	310	2,63	
13:17:55	0,00	4,65	312	2,57	
13:18:25	0,00	4,65	318	2,84	
13:18:55	0,00	4,77	310	2,78	
13:19:25	0,00	4,68	310	2,75	
13:19:55	0,00	4,62	310	2,72	
13:20:25	0,00	4,65	310	2,66	
13:20:55	0,00	4,65	310	2,63	
13:21:25	0,00	4,65	314	2,60	
13:21:55	0,00	4,74	308	2,84	
13:22:25	0,00	4,62	316	2,81	
13:22:55	0,00	4,74	310	2,75	
13:23:25	0,00	4,65	310	2,72	
13:23:55	0,00	4,68	308	2,66	
13:24:25	0,00	4,65	310	2,63	
13:24:55	0,00	4,62	310	2,57	
13:25:25	0,00	4,77	308	2,84	
13:25:55	0,00	4,62	316	2,78	
13:26:25	0,00	4,68	308	2,75	
13:26:55	0,00	4,65	310	2,69	
13:27:25	0,00	4,65	310	2,66	
13:27:55	0,00	4,62	308	2,66	
13:28:25	0,00	4,74	308	2,63	
13:28:55	0,00	4,77	308	2,84	
13:29:25	0,00	4,65	308	2,78	
13:29:55	0,00	4,74	308	2,75	
13:30:25	0,00	4,65	308	2,72	
13:30:55	0,00	4,62	308	2,66	
13:31:25	0,00	4,65	314	2,60	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
13:31:55	0,00	4,65	314	2,84	
13:32:25	0,00	4,62	308	2,84	
13:32:55	0,00	4,77	308	2,75	
13:33:25	0,00	4,65	310	2,72	
13:33:55	0,00	4,65	308	2,69	
13:34:25	0,00	4,65	310	2,66	
13:34:55	0,00	4,62	316	2,57	
13:35:25	0,00	4,65	308	2,81	
13:35:55	0,00	4,77	308	2,84	
13:36:25	0,00	4,62	308	2,75	
13:36:55	0,00	4,65	314	2,72	
13:37:25	0,00	4,62	308	2,66	
13:37:55	0,00	4,65	314	2,66	
13:38:25	0,00	4,77	308	2,57	
13:38:55	0,00	4,62	308	2,84	
13:39:25	0,00	4,62	310	2,81	
13:39:55	0,00	4,65	308	2,75	
13:40:25	0,00	4,65	308	2,72	
13:40:55	0,00	4,62	318	2,66	
13:41:25	0,00	4,71	308	2,63	
13:41:55	0,00	4,65	318	2,57	
13:42:25	0,00	4,65	310	2,84	
13:42:55	0,00	4,65	316	2,81	
13:43:25	0,00	4,65	314	2,78	
13:43:55	0,00	4,65	308	2,72	
13:44:25	0,00	4,71	308	2,66	
13:44:55	0,00	4,65	310	2,63	
13:45:25	0,00	4,65	310	2,57	
13:45:55	0,00	4,65	318	2,81	
13:46:25	0,00	4,77	308	2,84	
13:46:55	0,00	4,65	308	2,75	
13:47:25	0,00	4,62	308	2,72	
13:47:55	0,00	4,77	308	2,66	
13:48:25	0,00	4,74	308	2,63	
13:48:55	0,00	4,65	308	2,66	
13:49:25	0,00	4,71	305	2,84	
13:49:55	0,00	4,65	314	2,78	
13:50:25	0,00	4,62	310	2,75	
13:50:55	0,00	4,62	310	2,72	
13:51:25	0,00	4,71	308	2,66	
13:51:55	0,00	4,65	318	2,63	
13:52:25	0,00	4,71	308	2,72	
13:52:55	0,00	4,65	310	2,84	
13:53:25	0,00	4,68	310	2,78	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
13:53:55	0,00	4,62	308	2,75	
13:54:25	0,00	4,74	308	2,69	
13:54:55	0,00	4,77	308	2,63	
13:55:25	0,00	4,74	308	2,60	
13:55:55	0,00	4,62	310	2,75	
13:56:25	0,00	4,74	308	2,84	
13:56:55	0,00	4,77	308	2,78	
13:57:25	0,00	4,68	310	2,72	
13:57:55	0,00	4,65	308	2,69	
13:58:25	0,00	4,74	308	2,69	
13:58:55	0,00	4,65	308	2,57	
13:59:25	0,00	4,65	308	2,84	
13:59:55	0,00	4,65	308	2,81	
14:00:25	0,00	4,65	310	2,75	
14:00:55	0,00	4,62	308	2,72	
14:01:25	0,00	4,65	308	2,66	
14:01:55	0,00	4,65	308	2,66	
14:02:25	0,00	4,65	318	2,57	
14:02:55	0,00	4,65	310	2,84	
14:03:25	0,00	4,71	308	2,81	
14:03:55	0,00	4,74	310	2,78	
14:04:25	0,00	4,65	310	2,75	
14:04:55	0,00	4,65	308	2,66	
14:05:25	0,00	4,77	308	2,63	
14:05:55	0,00	4,62	310	2,57	
14:06:25	0,00	4,65	316	2,84	
14:06:55	0,00	4,65	308	2,81	
14:07:25	0,00	4,65	310	2,75	
14:07:55	0,00	4,65	308	2,72	
14:08:25	0,00	4,62	310	2,69	
14:08:55	0,00	4,65	310	2,63	
14:09:25	0,00	4,65	314	2,63	
14:09:55	0,00	4,62	308	2,84	
14:10:25	0,00	4,62	308	2,81	
14:10:55	0,00	4,74	308	2,75	
14:11:25	0,00	4,74	310	2,69	
14:11:55	0,00	4,65	308	2,69	
14:12:25	0,00	4,71	308	2,60	
14:12:55	0,00	4,65	308	2,72	
14:13:25	0,00	4,62	310	2,84	
14:13:55	0,00	4,65	308	2,78	
14:14:25	0,00	4,62	310	2,75	
14:14:55	0,00	4,65	314	2,72	
14:15:25	0,00	4,65	318	2,66	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
14:15:55	0,00	4,65	316	2,63	
14:16:25	0,00	4,65	308	2,66	
14:16:55	0,00	4,62	310	2,84	
14:17:25	0,00	4,62	326	2,78	
14:17:55	0,00	4,62	308	2,72	
14:18:25	0,00	4,62	318	2,66	
14:18:55	0,00	4,74	310	2,60	
14:19:25	0,00	4,65	308	2,69	
14:19:55	0,00	4,87	308	2,75	
14:20:25	0,00	4,74	308	2,84	
14:20:55	0,00	4,62	308	2,84	
14:21:25	0,00	0,00	0,00	2,81	
14:21:55	0,00	0,00	0,00	2,81	
14:22:25	0,00	0,00	0,00	2,81	

Time hh:mm:ss	Xe Feed Unit Input	Primary Xe Feed Branch	Redundant Xe Feed Branch	Xe Storage Unit 1	Xe Storage Unit 2	Xe Storage Unit 3	Xe Feed Unit	Thruster Unit 4
	Pressure (kgf/cm ²)			Temperature (°C)				
13:01:24	59,00	4,81	4,02	13,25	11,68	14,29	16,86	15,35
14:12:17	59,00	4,67	4,02	13,25	11,68	14,29	16,86	15,35

Annex 4. RT4C2 Thruster Operation TM-data based on available TM-data receipt sessions (13/02/01)

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
12:11:08	0,00	0,00	0,00	2,78	
12:11:18	0,00	0,00	0,00	2,78	
12:11:28	0,00	0,00	0,00	2,78	
12:11:38	0,00	0,00	0,00	2,78	
12:11:48	0,00	0,00	346	2,78	
12:11:58	12,00	0,00	322	2,78	
12:12:08	11,90	0,00	322	2,78	
12:12:18	12,00	0,00	322	2,78	
12:12:28	12,30	0,00	322	2,78	
12:12:38	12,10	0,00	322	2,78	
12:12:48	12,00	0,00	322	2,78	
12:12:58	12,00	0,00	322	2,78	
12:13:08	11,90	0,00	322	2,78	
12:13:18	11,90	0,00	322	2,78	
12:13:28	12,00	0,00	322	2,78	
12:13:38	12,00	0,00	322	2,78	
12:13:48	12,00	0,00	322	2,78	
12:13:58	12,00	0,00	322	2,78	
12:14:08	12,00	0,00	322	2,78	
12:14:18	12,00	0,00	322	2,78	
12:14:28	12,00	0,00	322	2,78	
12:14:38	0,00	3,79	308	2,78	
12:15:08	0,00	4,62	305	2,75	
12:15:38	0,00	4,56	308	2,69	
12:16:08	0,00	4,62	308	2,66	
12:16:38	0,00	4,65	308	2,63	
12:17:08	0,00	4,65	308	2,72	
12:17:38	0,00	4,65	314	2,81	
12:18:08	0,00	4,65	308	2,75	
12:18:38	0,00	4,65	308	2,72	
12:19:08	0,00	4,65	308	2,69	
12:19:38	0,00	4,65	305	2,63	
12:20:08	0,00	4,65	305	2,63	
12:20:38	0,00	4,68	310	2,84	
12:21:08	0,00	4,65	310	2,78	
12:21:38	0,00	4,62	310	2,75	
12:22:08	0,00	4,77	308	2,72	
12:22:38	0,00	4,62	308	2,66	
12:23:08	0,00	4,65	308	2,63	
12:23:38	0,00	4,65	318	2,78	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
12:24:08	0,00	4,62	310	2,84	
12:24:38	0,00	4,62	308	2,75	
12:25:08	0,00	4,62	308	2,72	
12:25:38	0,00	4,65	308	2,66	
12:26:08	0,00	4,77	308	2,63	
12:26:38	0,00	4,59	318	2,57	
12:27:08	0,00	4,62	308	2,78	
12:27:38	0,00	4,62	308	2,84	
12:28:08	0,00	4,77	308	2,75	
12:28:38	0,00	4,62	310	2,72	
12:29:08	0,00	4,62	308	2,66	
12:29:38	0,00	4,65	308	2,66	
12:30:08	0,00	4,62	310	2,57	
12:30:38	0,00	4,65	308	2,78	
12:31:08	0,00	4,62	310	2,84	
12:31:38	0,00	4,77	308	2,75	
12:32:08	0,00	4,77	308	2,72	
12:32:38	0,00	4,62	308	2,66	
12:33:08	0,00	4,65	308	2,66	
12:33:38	0,00	4,65	308	2,57	
12:34:08	0,00	4,65	316	2,81	
12:34:38	0,00	4,65	318	2,84	
12:35:08	0,00	4,65	310	2,75	
12:35:38	0,00	4,62	308	2,72	
12:36:08	0,00	4,62	318	2,66	
12:36:38	0,00	4,62	305	2,63	
12:37:08	0,00	4,62	310	2,57	
12:37:38	0,00	4,62	310	2,84	
12:38:08	0,00	4,62	308	2,81	
12:38:38	0,00	4,62	308	2,75	
12:39:08	0,00	4,65	310	2,72	
12:39:38	0,00	4,65	308	2,66	
12:40:08	0,00	4,71	308	2,63	
12:40:38	0,00	4,65	305	2,57	
12:41:08	0,00	4,62	310	2,84	
12:41:38	0,00	4,62	308	2,81	
12:42:08	0,00	4,65	308	2,75	
12:42:38	0,00	4,62	308	2,69	
12:43:08	0,00	4,65	308	2,66	
12:43:38	0,00	4,65	308	2,63	
12:44:08	0,00	4,59	305	2,60	
12:44:38	0,00	4,62	305	2,84	
12:45:08	0,00	4,68	308	2,78	
12:45:38	0,00	4,59	310	2,75	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
12:46:08	0,00	4,65	308	2,69	
12:46:38	0,00	4,65	308	2,66	
12:47:08	0,00	4,62	308	2,63	
12:47:38	0,00	4,62	308	2,63	
12:48:08	0,00	4,65	308	2,84	
12:48:38	0,00	4,65	310	2,78	
12:49:08	0,00	4,62	308	2,75	
12:49:38	0,00	4,77	308	2,69	
12:50:08	0,00	4,65	308	2,66	
12:50:38	0,00	4,62	308	2,63	
12:51:08	0,00	4,65	310	2,66	
12:51:38	0,00	4,65	305	2,84	
12:52:08	0,00	4,65	318	2,78	
12:52:38	0,00	4,65	305	2,75	
12:53:08	0,00	4,62	308	2,72	
12:53:38	0,00	4,65	308	2,69	
12:54:08	0,00	4,77	308	2,63	
12:54:38	0,00	4,71	308	2,66	
12:55:08	0,00	4,65	314	2,84	
12:55:38	0,00	4,62	310	2,78	
12:56:08	0,00	4,62	308	2,75	
12:56:38	0,00	4,62	305	2,72	
12:57:08	0,00	4,65	310	2,69	
12:57:38	0,00	4,74	308	2,66	
12:58:08	0,00	4,62	308	2,72	
12:58:38	0,00	4,62	308	2,84	
12:59:08	0,00	4,62	308	2,78	
12:59:38	0,00	4,62	308	2,75	
13:00:08	0,00	4,59	318	2,72	
13:00:38	0,00	4,65	305	2,66	
13:01:08	0,00	4,62	318	2,60	
13:01:38	0,00	4,62	305	2,72	
13:02:08	0,00	4,65	314	2,84	
13:02:38	0,00	4,77	308	2,78	
13:03:08	0,00	4,65	314	2,75	
13:03:38	0,00	4,65	316	2,72	
13:04:08	0,00	4,65	318	2,66	
13:04:38	0,00	4,65	316	2,60	
13:05:08	0,00	4,71	305	2,72	
13:05:38	0,00	4,65	305	2,84	
13:06:08	0,00	4,77	308	2,78	
13:06:38	0,00	4,62	308	2,72	
13:07:08	0,00	4,65	308	2,69	
13:07:38	0,00	4,74	308	2,66	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
13:08:08	0,00	4,62	305	2,60	
13:08:38	0,00	4,62	308	2,75	
13:09:08	0,00	4,62	310	2,84	
13:09:38	0,00	4,65	308	2,78	
13:10:08	0,00	4,65	310	2,69	
13:10:38	0,00	4,65	318	2,66	
13:11:08	0,00	4,65	308	2,66	
13:11:38	0,00	4,77	308	2,57	
13:12:08	0,00	4,65	305	2,75	
13:12:38	0,00	4,65	308	2,84	
13:13:08	0,00	4,62	310	2,75	
13:13:38	0,00	4,74	310	2,72	
13:14:08	0,00	4,62	308	2,69	
13:14:38	0,00	4,62	308	2,63	
13:15:08	0,00	4,65	310	2,84	
13:15:38	0,00	4,65	310	2,78	
13:16:08	0,00	4,65	308	2,84	
13:16:38	0,00	4,68	308	2,75	
13:17:08	0,00	4,62	308	2,72	
13:17:38	0,00	4,62	310	2,66	
13:18:08	0,00	4,65	308	2,63	
13:18:38	0,00	4,62	308	2,57	
13:19:08	0,00	4,65	308	2,78	
13:19:38	0,00	4,65	308	2,84	
13:20:08	0,00	4,62	310	2,75	
13:20:38	0,00	4,65	308	2,72	
13:21:08	0,00	4,65	318	2,66	
13:21:38	0,00	4,68	308	2,63	
13:22:08	0,00	4,65	308	2,57	
13:22:38	0,00	4,68	305	2,84	
13:23:08	0,00	4,62	310	2,84	
13:23:38	0,00	4,62	310	2,75	
13:24:08	0,00	4,65	308	2,69	
13:24:38	0,00	4,62	308	2,66	
13:25:08	0,00	4,77	308	2,66	
13:25:38	0,00	4,65	308	2,57	
13:26:08	0,00	4,65	308	2,84	
13:26:38	0,00	0,00	0,00	2,81	
13:27:08	0,00	0,00	0,00	2,81	
13:27:38	0,00	0,00	0,00	2,81	

Time hh:mm:ss	Xe Feed Unit Input	Primary Xe Feed Branch	Redundant Xe Feed Branch	Xe Storage Unit 1	Xe Storage Unit 2	Xe Storage Unit 3	Xe Feed Unit	Thruster Unit 4
	Pressure (kgf/cm ²)			Temperature (°C)				
12:11:04	56,36	4,88	4,09	12,72	11,15	13,25	16,34	12,02
12:51:07	56,36	4,88	4,09	12,72	11,15	13,25	16,34	15,35
13:19:01	56,36	4,74	4,09	12,72	11,15	13,25	16,34	15,35
13:22:21	56,36	4,67	4,09	12,72	11,15	13,25	16,34	15,35
13:22:54	56,36	4,67	4,09	12,72	11,15	13,25	16,34	18,68
13:25:52	56,36	4,52	4,09	12,72	11,15	13,25	16,34	18,68

Annex 5. T4C2 Thruster Operation TM-data based on available TM-data receipt sessions (22/02/01)

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
11:34:31	0,00	0,00	0,00	2,75	
11:34:41	0,00	0,00	0,00	2,75	
11:34:51	0,00	0,00	0,00	2,84	
11:35:01	0,00	0,00	0,00	2,84	
11:35:11	0,00	0,00	0,00	2,84	
11:35:21	0,00	0,00	0,00	2,84	
11:35:31	0,00	0,00	0,00	2,84	
11:35:41	0,00	0,00	0,00	2,84	
11:35:51	0,00	0,00	0,00	2,84	
11:36:01	0,00	0,00	0,00	2,84	
11:36:11	0,00	0,00	0,00	2,84	
11:36:21	0,00	0,00	346	2,84	
11:36:31	12,20	0,00	326	2,84	
11:36:41	12,00	0,00	326	2,84	
11:36:51	12,00	0,00	326	2,84	
11:37:01	12,00	0,00	326	2,84	
11:37:11	12,10	0,00	326	2,84	
11:37:21	12,10	0,00	326	2,84	
11:37:31	12,00	0,00	326	2,84	
11:37:41	12,00	0,00	326	2,84	
11:37:51	12,00	0,00	326	2,84	
11:38:01	12,10	0,00	326	2,84	
11:38:11	12,30	0,00	326	2,84	
11:38:21	12,10	0,00	326	2,84	
11:38:31	12,10	0,00	326	2,84	
11:38:41	12,00	0,00	326	2,84	
11:38:51	12,00	0,00	326	2,84	
11:39:01	0,00	4,07	310	2,81	
11:39:31	0,00	4,65	310	2,72	
11:40:01	0,00	4,65	308	2,72	
11:40:31	0,00	4,40	312	2,66	
11:41:01	0,00	4,62	310	2,63	
11:41:31	0,00	4,77	308	2,81	
11:42:01	0,00	4,65	308	2,78	
11:42:31	0,00	4,65	308	2,72	
11:43:01	0,00	4,74	310	2,72	
11:43:31	0,00	4,62	310	2,66	
11:44:01	0,00	4,62	316	2,72	
11:44:31	0,00	4,62	310	2,81	
11:45:01	0,00	4,59	310	2,75	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
11:45:31	0,00	4,59	316	2,69	
11:46:01	0,00	4,62	310	2,66	
11:46:31	0,00	4,62	310	2,63	
11:47:01	0,00	4,62	310	2,66	
11:47:31	0,00	4,62	310	2,84	
11:48:01	0,00	4,65	316	2,78	
11:48:31	0,00	4,65	308	2,72	
11:49:01	0,00	4,62	308	2,69	
11:49:31	0,00	4,65	308	2,63	
11:50:01	0,00	4,65	308	2,60	
11:50:31	0,00	4,65	318	2,84	
11:51:01	0,00	4,71	310	2,78	
11:51:31	0,00	4,65	308	2,75	
11:52:01	0,00	4,65	308	2,69	
11:52:31	0,00	4,65	312	2,66	
11:53:01	0,00	4,62	326	2,75	
11:53:31	0,00	4,77	310	2,78	
11:54:01	0,00	4,62	310	2,75	
11:54:31	0,00	4,77	308	2,69	
11:55:01	0,00	4,65	310	2,66	
11:55:31	0,00	4,62	310	2,78	
11:56:01	0,00	4,65	318	2,78	
11:56:31	0,00	4,65	310	2,75	
11:57:01	0,00	4,59	310	2,69	
11:57:31	0,00	4,65	318	2,66	
11:58:01	0,00	4,65	318	2,84	
11:58:31	0,00	4,65	308	2,78	
11:59:01	0,00	4,65	308	2,75	
11:59:31	0,00	4,65	308	2,69	
12:00:01	0,00	4,65	308	2,63	
12:00:31	0,00	4,77	308	2,84	
12:01:01	0,00	4,77	308	2,78	
12:01:31	0,00	4,62	316	2,72	
12:02:01	0,00	4,65	308	2,66	
12:02:31	0,00	4,62	308	2,66	
12:03:01	0,00	4,62	308	2,81	
12:03:31	0,00	4,68	310	2,75	
12:04:01	0,00	4,65	310	2,72	
12:04:31	0,00	4,65	326	2,66	
12:05:01	0,00	4,68	308	2,66	
12:05:31	0,00	4,65	318	2,78	
12:06:01	0,00	4,77	308	2,75	
12:06:31	0,00	4,65	310	2,69	
12:07:01	0,00	4,65	314	2,66	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
12:07:31	0,00	4,65	305	2,66	
12:08:01	0,00	4,65	308	2,78	
12:08:31	0,00	4,62	314	2,75	
12:09:01	0,00	4,65	308	2,69	
12:09:31	0,00	4,65	308	2,66	
12:10:01	0,00	4,65	308	2,69	
12:10:31	0,00	4,65	318	2,78	
12:11:01	0,00	4,62	334	2,75	
12:11:31	0,00	4,62	310	2,69	
12:12:01	0,00	4,74	308	2,66	
12:12:31	0,00	4,65	316	2,63	
12:13:01	0,00	4,74	308	2,75	
12:13:31	0,00	4,74	308	2,81	
12:14:01	0,00	4,65	316	2,75	
12:14:31	0,00	4,77	308	2,69	
12:15:01	0,00	4,65	308	2,66	
12:15:31	0,00	4,62	308	2,63	
12:16:01	0,00	4,65	310	2,69	
12:16:31	0,00	4,65	316	2,84	
12:17:01	0,00	4,65	314	2,78	
12:17:31	0,00	4,65	318	2,72	
12:18:01	0,00	4,65	326	2,69	
12:18:31	0,00	4,77	308	2,63	
12:19:01	0,00	4,68	305	2,60	
12:19:31	0,00	4,87	310	2,84	
12:20:01	0,00	4,68	308	2,78	
12:20:31	0,00	4,56	308	2,75	
12:21:01	0,00	4,62	310	2,72	
12:21:31	0,00	4,65	326	2,66	
12:22:01	0,00	4,77	308	2,63	
12:22:31	0,00	4,62	310	2,78	
12:23:01	0,00	4,65	308	2,81	
12:23:31	0,00	4,65	326	2,75	
12:24:01	0,00	4,65	308	2,69	
12:24:31	0,00	4,65	316	2,66	
12:25:01	0,00	4,65	318	2,63	
12:25:31	0,00	4,62	308	2,72	
12:26:01	0,00	4,74	305	2,84	
12:26:31	0,00	4,62	310	2,78	
12:27:01	0,00	4,77	308	2,72	
12:27:31	0,00	4,65	308	2,66	
12:28:01	0,00	4,62	310	2,66	
12:28:31	0,00	4,65	310	2,60	
12:29:01	0,00	4,65	308	2,84	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
12:29:31	0,00	4,62	318	2,78	
12:30:01	0,00	4,77	308	2,75	
12:30:31	0,00	4,65	310	2,72	
12:31:01	0,00	4,74	310	2,66	
12:31:31	0,00	4,65	308	2,63	
12:32:01	0,00	4,65	314	2,78	
12:32:31	0,00	4,65	314	2,81	
12:33:01	0,00	4,62	310	2,75	
12:33:31	0,00	4,65	334	2,69	
12:34:01	0,00	4,62	310	2,66	
12:34:31	0,00	4,74	308	2,63	
12:35:01	0,00	4,68	308	2,72	
12:35:31	0,00	4,56	308	2,84	
12:36:01	0,00	4,62	308	2,75	
12:36:31	0,00	4,65	310	2,72	
12:37:01	0,00	4,77	310	2,69	
12:37:31	0,00	4,62	326	2,63	
12:38:01	0,00	4,65	308	2,66	
12:38:31	0,00	4,65	318	2,84	
12:39:01	0,00	4,65	308	2,75	
12:39:31	0,00	4,65	310	2,72	
12:40:01	0,00	4,65	310	2,69	
12:40:31	0,00	4,71	308	2,66	
12:41:01	0,00	4,68	308	2,60	
12:41:31	0,00	4,68	308	2,78	
12:42:01	0,00	4,62	308	2,81	
12:42:31	0,00	4,77	308	2,75	
12:43:01	0,00	4,62	310	2,69	
12:43:31	0,00	4,71	308	2,66	
12:44:01	0,00	4,62	310	2,63	
12:44:31	0,00	4,62	308	2,72	
12:45:01	0,00	4,62	305	2,84	
12:45:31	0,00	4,71	308	2,75	
12:46:01	0,00	4,65	308	2,72	
12:46:31	0,00	4,62	308	2,69	
12:47:01	0,00	4,65	326	2,63	
12:47:31	0,00	4,65	308	2,66	
12:48:01	0,00	4,77	308	2,84	
12:48:31	0,00	4,56	314	2,84	
12:49:01	0,00	4,62	314	2,78	
12:49:31	0,00	4,71	308	2,75	
12:50:01	0,00	4,74	305	2,72	
12:50:31	0,00	4,71	310	2,66	
12:51:01	0,00	4,62	310	2,63	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
12:51:31	0,00	0,00	0,00	2,84	
13:00:01	0,00	0,00	0,00	2,84	
13:00:31	0,00	0,00	0,00	2,84	

Time hh:mm:ss	Xe Feed Unit Input	Primary Xe Feed Branch	Redundant Xe Feed Branch	Xe Storage Unit 1	Xe Storage Unit 2	Xe Storage Unit 3	Xe Feed Unit	Thruster Unit 4
	Pressure (kgf/cm ²)			Temperature (°C)				
10:52:24	55,05	4,67	4,02	11,68	11,15	12,20	14,77	10,69
12:21:01	55,05	4,67	4,02	11,68	11,15	12,20	17,38	10,69
12:28:27	55,05	4,67	4,02	11,68	11,15	12,20	17,38	14,02
12:41:37	55,05	4,74	4,02	11,68	11,15	12,20	17,38	14,02
12:44:25	55,05	4,67	4,02	11,68	11,15	12,20	17,38	14,02
12:47:48	55,05	4,59	4,02	11,68	11,15	12,20	17,38	14,02

Annex 6. T4C2 Thruster Operation TM-data based on available TM-data receipt sessions (28/02/01)

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
11:11:27	0,00	0,00	0,00	2,81	
11:11:37	0,00	0,00	0,00	2,81	
11:11:47	0,00	0,00	0,00	2,81	
11:11:57	0,00	0,00	0,00	2,81	
11:12:07	0,00	0,00	0,00	2,81	
11:12:17	0,00	0,00	0,00	2,81	
11:12:27	0,00	0,00	0,00	2,81	
11:12:37	0,00	0,00	346	2,81	
11:12:47	12,20	0,00	326	2,81	
11:12:57	12,00	0,00	326	2,81	
11:13:07	12,00	0,00	326	2,81	
11:13:17	12,00	0,00	326	2,81	
11:13:27	12,10	0,00	326	2,81	
11:13:37	12,10	0,00	326	2,81	
11:13:47	12,00	0,00	326	2,81	
11:13:57	12,00	0,00	326	2,81	
11:14:07	11,90	0,00	326	2,81	
11:14:17	12,10	0,00	326	2,81	
11:14:27	12,20	0,00	326	2,81	
11:14:37	12,20	0,00	326	2,81	
11:14:47	12,10	0,00	326	2,81	
11:14:57	12,00	0,00	326	2,81	
11:15:07	12,00	0,00	326	2,81	
11:15:17	12,00	0,00	326	2,81	
11:15:27	0,00	4,59	308	2,78	
11:15:47	0,00	4,65	308	2,75	
11:16:17	0,00	4,62	310	2,72	
11:16:47	0,00	4,65	316	2,66	
11:17:17	0,00	4,87	308	2,63	
11:17:47	0,00	4,68	308	2,63	
11:18:17	0,00	4,65	308	2,84	
11:18:47	0,00	4,59	308	2,78	
11:19:17	0,00	4,56	308	2,75	
11:19:47	0,00	4,80	305	2,69	
11:20:17	0,00	4,53	310	2,66	
11:20:47	0,00	4,62	310	2,63	
11:21:17	0,00	4,65	310	2,72	
11:21:47	0,00	4,77	310	2,84	
11:22:17	0,00	4,71	310	2,78	
11:22:47	0,00	4,65	318	2,72	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
11:23:17	0,00	4,65	316	2,66	
11:23:47	0,00	4,74	308	2,66	
11:24:17	0,00	4,62	310	2,63	
11:24:47	0,00	4,62	308	2,84	
11:25:17	0,00	4,65	310	2,78	
11:25:47	0,00	4,65	310	2,75	
11:26:17	0,00	4,68	310	2,69	
11:26:47	0,00	4,68	310	2,69	
11:27:17	0,00	4,65	316	2,63	
11:27:47	0,00	4,77	308	2,63	
11:28:17	0,00	4,65	318	2,84	
11:28:47	0,00	4,65	316	2,78	
11:29:17	0,00	4,65	310	2,75	
11:29:47	0,00	4,65	308	2,69	
11:30:17	0,00	4,62	326	2,66	
11:30:47	0,00	4,62	310	2,63	
11:31:17	0,00	4,65	318	2,63	
11:31:47	0,00	4,65	314	2,87	
11:32:17	0,00	4,74	308	2,78	
11:32:47	0,00	4,65	310	2,72	
11:33:17	0,00	4,62	310	2,69	
11:33:47	0,00	4,65	314	2,69	
11:34:17	0,00	4,71	308	2,63	
11:34:47	0,00	4,77	308	2,63	
11:35:17	0,00	4,65	308	2,84	
11:35:47	0,00	4,87	310	2,78	
11:36:17	0,00	4,77	308	2,75	
11:36:47	0,00	4,65	310	2,69	
11:37:17	0,00	4,74	308	2,63	
11:37:47	0,00	4,74	310	2,60	
11:38:17	0,00	4,62	308	2,84	
11:38:47	0,00	4,62	310	2,81	
11:39:17	0,00	4,68	308	2,75	
11:39:47	0,00	4,68	305	2,69	
11:40:17	0,00	4,65	308	2,69	
11:40:47	0,00	4,62	318	2,63	
11:41:17	0,00	4,77	308	2,78	
11:41:47	0,00	4,65	308	2,84	
11:42:17	0,00	4,68	310	2,75	
11:42:47	0,00	4,87	310	2,72	
11:43:17	0,00	4,62	326	2,66	
11:43:47	0,00	4,77	308	2,63	
11:44:17	0,00	4,74	308	2,69	
11:44:47	0,00	4,65	318	2,84	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
11:45:17	0,00	4,62	308	2,78	
11:45:47	0,00	4,74	308	2,72	
11:46:17	0,00	4,65	308	2,66	
11:46:47	0,00	4,65	314	2,66	
11:47:17	0,00	4,65	305	2,60	
11:47:47	0,00	4,74	308	2,84	
11:48:17	0,00	4,87	308	2,78	
11:48:47	0,00	4,65	308	2,75	
11:49:17	0,00	4,74	308	2,69	
11:49:47	0,00	4,62	318	2,66	
11:50:17	0,00	4,65	326	2,63	
11:50:47	0,00	4,65	310	2,60	
11:51:17	0,00	4,65	310	2,84	
11:51:47	0,00	4,62	334	2,78	
11:52:17	0,00	4,62	334	2,72	
11:52:47	0,00	4,65	316	2,66	
11:53:17	0,00	4,87	308	2,63	
11:53:47	0,00	4,71	308	2,57	
11:54:17	0,00	4,65	308	2,75	
11:54:47	0,00	4,74	308	2,84	
11:55:17	0,00	4,65	308	2,75	
11:55:47	0,00	4,68	308	2,69	
11:56:17	0,00	4,71	308	2,66	
11:56:47	0,00	4,65	310	2,63	
11:57:17	0,00	4,65	308	2,69	
11:57:47	0,00	4,87	308	2,84	
11:58:17	0,00	4,62	310	2,78	
11:58:47	0,00	4,71	308	2,72	
11:59:17	0,00	4,62	308	2,69	
11:59:47	0,00	4,71	308	2,66	
12:00:17	0,00	4,62	308	2,63	
12:00:47	0,00	4,62	310	2,84	
12:01:17	0,00	4,68	310	2,78	
12:01:47	0,00	4,65	308	2,75	
12:02:17	0,00	4,77	308	2,72	
12:02:47	0,00	4,62	318	2,66	
12:03:17	0,00	4,65	318	2,63	
12:03:47	0,00	4,65	308	2,78	
12:04:17	0,00	4,62	314	2,84	
12:04:47	0,00	4,65	310	2,75	
12:05:17	0,00	4,74	308	2,69	
12:05:47	0,00	4,62	310	2,66	
12:06:17	0,00	4,62	308	2,66	
12:06:47	0,00	4,71	308	2,57	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
12:07:17	0,00	4,62	310	2,78	
12:07:47	0,00	4,77	308	2,84	
12:08:17	0,00	4,65	310	2,75	
12:08:47	0,00	4,65	310	2,72	
12:09:17	0,00	4,65	314	2,69	
12:09:47	0,00	4,62	318	2,66	
12:10:17	0,00	4,71	308	2,57	
12:10:47	0,00	4,71	310	2,81	
12:11:17	0,00	4,71	308	2,84	
12:11:47	0,00	4,62	316	2,75	
12:12:17	0,00	4,68	310	2,72	
12:12:47	0,00	4,68	310	2,66	
12:13:17	0,00	4,65	318	2,63	
12:13:47	0,00	4,62	308	2,63	
12:14:17	0,00	4,62	310	2,84	
12:14:47	0,00	4,65	308	2,78	
12:15:17	0,00	4,62	310	2,75	
12:15:47	0,00	4,65	308	2,69	
12:16:17	0,00	4,62	312	2,66	
12:16:47	0,00	4,59	308	2,63	
12:17:17	0,00	4,59	316	2,75	
12:17:47	0,00	4,65	308	2,84	
12:18:17	0,00	4,62	326	2,78	
12:18:47	0,00	4,62	326	2,72	
12:19:17	0,00	4,65	318	2,69	
12:19:47	0,00	4,65	308	2,63	
12:20:17	0,00	4,65	316	2,60	
12:20:47	0,00	4,62	318	2,75	
12:21:17	0,00	4,65	318	2,84	
12:21:47	0,00	4,65	308	2,78	
12:22:17	0,00	4,62	314	2,75	
12:22:47	0,00	4,65	310	2,66	
12:23:17	0,00	4,87	308	2,63	
12:23:47	0,00	4,62	316	2,60	
12:24:17	0,00	4,62	310	2,81	
12:24:47	0,00	4,62	310	2,84	
12:25:17	0,00	4,62	318	2,75	
12:25:47	0,00	4,65	316	2,72	
12:26:17	0,00	4,77	308	2,66	
12:26:47	0,00	4,65	310	2,62	
12:27:17	0,00	4,65	308	2,57	
12:27:47	0,00	0,00	0,00	2,66	
12:28:17	0,00	0,00	0,00	2,66	
12:28:47	0,00	0,00	0,00	2,66	

Time hh:mm:ss	Xe Feed Unit Input	Primary Xe Feed Branch	Redundant Xe Feed Branch	Xe Storage Unit 1	Xe Storage Unit 2	Xe Storage Unit 3	Xe Feed Unit	Thruster Unit 4
	Pressure (kgf/cm ²)			Temperature (°C)				
11:11:24	55,05	4,81	4,09	11,68	11,15	11,68	15,29	9,36
12:09:17	55,05	4,81	4,09	11,68	11,15	11,68	15,29	12,69
12:20:39	55,05	4,67	4,09	11,68	11,15	11,68	15,29	12,69
12:23:58	55,05	4,59	4,09	11,68	11,15	11,68	15,29	12,69

Annex 7. T4C2 Thruster Operation TM-data based on available TM-data receipt sessions (04/03/01)

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
10:55:54	0,00	0,00	0,00	2,78	
10:56:04	0,00	0,00	0,00	2,78	
10:56:14	0,00	0,00	0,00	2,78	
10:56:24	0,00	0,00	0,00	2,78	
10:56:34	0,00	0,00	0,00	2,78	
10:56:44	0,00	0,00	0,00	2,78	
10:56:54	12,30	0,00	326	2,78	
10:57:04	12,00	0,00	326	2,78	
10:57:14	12,00	0,00	326	2,78	
10:57:24	12,00	0,00	326	2,78	
10:57:34	12,10	0,00	326	2,78	
10:57:44	12,20	0,00	326	2,78	
10:57:54	12,00	0,00	326	2,78	
10:58:04	12,00	0,00	326	2,78	
10:58:14	11,90	0,00	326	2,78	
10:58:24	12,00	0,00	326	2,78	
10:58:34	12,20	0,00	326	2,78	
10:58:44	12,20	0,00	326	2,78	
10:58:54	12,00	0,00	326	2,78	
10:59:04	12,00	0,00	326	2,78	
10:59:14	12,00	0,00	326	2,78	
10:59:24	12,00	0,00	326	2,78	
10:59:34	12,10	0,00	326	2,78	
10:59:44	11,90	0,00	326	2,78	
10:59:54	0,00	4,77	308	2,75	
11:00:24	0,00	4,65	310	2,69	
11:00:54	0,00	4,59	316	2,65	
11:01:24	0,00	4,10	312	2,63	
11:01:54	0,00	4,13	310	2,57	
11:02:24	0,00	4,25	310	2,78	
11:02:54	0,00	4,71	308	2,81	
11:03:24	0,00	4,62	308	2,75	
11:03:54	0,00	4,77	305	2,72	
11:04:24	0,00	4,68	308	2,66	
11:04:54	0,00	4,74	310	2,63	
11:05:24	0,00	4,65	316	2,66	
11:05:54	0,00	4,65	312	2,84	
11:06:24	0,00	4,62	310	2,78	
11:06:54	0,00	4,65	310	2,75	
11:07:24	0,00	4,62	310	2,69	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
11:07:54	0,00	4,65	314	2,66	
11:08:24	0,00	4,65	314	2,60	
11:08:54	0,00	4,62	310	2,84	
11:09:24	0,00	4,65	310	2,78	
11:09:54	0,00	4,62	310	2,75	
11:10:24	0,00	4,62	314	2,69	
11:10:54	0,00	4,62	310	2,66	
11:11:24	0,00	4,62	310	2,63	
11:11:54	0,00	4,65	312	2,75	
11:12:24	0,00	4,65	310	2,84	
11:12:54	0,00	4,62	314	2,75	
11:13:24	0,00	4,74	310	2,72	
11:13:54	0,00	4,65	316	2,66	
11:14:24	0,00	4,65	318	2,63	
11:14:54	0,00	4,65	308	2,66	
11:15:24	0,00	4,65	308	2,84	
11:15:54	0,00	4,68	308	2,78	
11:16:24	0,00	4,74	308	2,72	
11:16:54	0,00	4,65	308	2,69	
11:17:24	0,00	4,65	326	2,63	
11:17:54	0,00	4,77	308	2,60	
11:18:24	0,00	4,62	318	2,84	
11:18:54	0,00	4,65	316	2,78	
11:19:24	0,00	4,65	310	2,75	
11:19:54	0,00	4,74	310	2,72	
11:20:24	0,00	4,77	308	2,66	
11:20:54	0,00	4,77	310	2,60	
11:21:24	0,00	4,65	310	2,75	
11:21:54	0,00	4,65	314	2,84	
11:22:24	0,00	4,68	308	2,75	
11:22:54	0,00	4,87	308	2,72	
11:23:24	0,00	4,68	308	2,66	
11:23:54	0,00	4,62	308	2,63	
11:24:24	0,00	4,65	308	2,66	
11:24:54	0,00	4,65	316	2,84	
11:25:24	0,00	4,65	318	2,78	
11:25:54	0,00	4,62	308	2,72	
11:26:24	0,00	4,68	310	2,69	
11:26:54	0,00	4,65	308	2,66	
11:27:24	0,00	4,62	308	2,60	
11:27:54	0,00	4,65	308	2,84	
11:28:24	0,00	4,65	308	2,75	
11:28:54	0,00	4,65	310	2,75	
11:29:24	0,00	4,62	308	2,69	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
11:29:54	0,00	4,65	316	2,66	
11:30:24	0,00	4,65	308	2,63	
11:30:54	0,00	4,87	308	2,75	
11:31:24	0,00	4,62	318	2,84	
11:31:54	0,00	4,62	316	2,75	
11:32:24	0,00	4,65	308	2,72	
11:32:54	0,00	4,65	318	2,66	
11:33:24	0,00	4,74	308	2,63	
11:33:54	0,00	4,62	318	2,66	
11:34:24	0,00	4,65	308	2,84	
11:34:54	0,00	4,65	308	2,78	
11:35:24	0,00	4,62	308	2,75	
11:35:54	0,00	4,65	318	2,69	
11:36:24	0,00	4,71	308	2,66	
11:36:54	0,00	4,65	314	2,60	
11:37:24	0,00	4,62	308	2,78	
11:37:54	0,00	4,62	314	2,81	
11:38:24	0,00	4,65	308	2,75	
11:38:54	0,00	4,71	308	2,69	
11:39:24	0,00	4,74	308	2,66	
11:39:54	0,00	4,62	310	2,63	
11:40:24	0,00	4,65	308	2,72	
11:40:54	0,00	4,65	308	2,87	
11:41:24	0,00	4,62	334	2,75	
11:41:54	0,00	4,65	316	2,72	
11:42:24	0,00	4,77	308	2,66	
11:42:54	0,00	4,65	310	2,63	
11:43:24	0,00	4,87	308	2,63	
11:43:54	0,00	4,65	308	2,84	
11:44:24	0,00	4,77	308	2,78	
11:44:54	0,00	4,65	308	2,75	
11:45:24	0,00	4,65	316	2,69	
11:45:54	0,00	4,65	308	2,66	
11:46:24	0,00	4,62	308	2,63	
11:46:54	0,00	4,65	310	2,81	
11:47:24	0,00	4,62	310	2,84	
11:47:54	0,00	4,62	308	2,75	
11:48:24	0,00	4,65	305	2,72	
11:48:54	0,00	4,65	308	2,69	
11:49:24	0,00	4,65	308	2,63	
11:49:54	0,00	4,77	308	2,57	
11:50:24	0,00	4,68	310	2,78	
11:50:54	0,00	4,65	308	2,84	
11:51:24	0,00	4,74	308	2,75	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
11:51:54	0,00	4,62	318	2,69	
11:52:24	0,00	4,71	308	2,69	
11:52:54	0,00	4,62	308	2,66	
11:53:24	0,00	4,65	314	2,60	
11:53:54	0,00	4,74	308	2,75	
11:54:24	0,00	4,65	318	2,84	
11:54:54	0,00	4,65	316	2,78	
11:55:24	0,00	4,62	308	2,72	
11:55:54	0,00	4,68	316	2,69	
11:56:24	0,00	4,62	310	2,63	
11:56:54	0,00	4,62	310	2,57	
11:57:24	0,00	4,65	318	2,75	
11:57:54	0,00	4,74	308	2,84	
11:58:24	0,00	4,68	308	2,75	
11:58:54	0,00	4,62	310	2,69	
11:59:24	0,00	4,77	308	2,66	
11:59:54	0,00	4,65	308	2,63	
12:00:24	0,00	4,62	326	2,69	
12:00:54	0,00	4,74	308	2,84	
12:01:24	0,00	4,68	318	2,78	
12:01:54	0,00	4,65	326	2,72	
12:02:24	0,00	4,74	308	2,69	
12:02:54	0,00	4,74	308	2,63	
12:03:24	0,00	4,77	308	2,60	
12:03:54	0,00	4,65	308	2,84	
12:04:24	0,00	4,65	308	2,81	
12:04:54	0,00	4,87	305	2,75	
12:05:24	0,00	4,74	308	2,69	
12:05:54	0,00	4,65	314	2,66	
12:06:24	0,00	4,65	310	2,63	
12:06:54	0,00	4,65	318	2,57	
12:07:24	0,00	4,87	308	2,84	
12:07:54	0,00	4,62	316	2,81	
12:08:24	0,00	4,62	308	2,75	
12:08:54	0,00	4,62	310	2,69	
12:09:24	0,00	4,65	314	2,69	
12:09:54	0,00	4,62	314	2,69	
12:10:24	0,00	4,65	308	2,78	
12:10:54	0,00	4,62	310	2,75	
12:11:24	0,00	4,65	308	2,69	
12:11:54	0,00	0,00	0,00	2,66	
12:12:24	0,00	0,00	0,00	2,66	
12:12:54	0,00	0,00	0,00	2,66	

Time hh:mm:ss	Xe Feed Unit Input	Primary Xe Feed Branch	Redundant Xe Feed Branch	Xe Storage Unit 1	Xe Storage Unit 2	Xe Storage Unit 3	Xe Feed Unit	Thruster Unit 1
	Pressure (kgf/cm ²)			Temperature (°C)				
10:55:45	55,05	4,81	4,09	11,15	11,15	11,15	15,29	9,36
11:58:35	55,05	4,81	4,09	11,15	11,15	11,15	15,29	12,69
12:03:31	55,05	4,74	4,09	11,15	11,15	11,15	15,29	12,69
12:06:57	55,05	4,67	4,09	11,15	11,15	11,15	15,29	12,69
12:09:49	55,05	4,59	4,09	11,15	11,15	11,15	15,29	12,69

Annex 8. T4C2 Thruster Operation TM-data based on available TM-data receipt sessions (08/03/01)

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
10:38:33	0,00	0,00	0,00	2,84	
10:38:43	0,00	0,00	0,00	2,84	
10:38:53	0,00	0,00	0,00	2,84	
10:39:03	0,00	0,00	0,00	2,84	
10:39:13	0,00	0,00	0,00	2,84	
10:39:23	0,00	0,00	0,00	2,84	
10:39:33	0,00	0,00	0,00	2,84	
10:39:43	0,00	0,00	0,00	2,84	
10:39:53	0,00	0,00	0,00	2,84	
10:40:03	0,00	0,00	0,00	2,84	
10:40:13	0,00	0,00	0,00	2,84	
10:40:23	0,00	0,00	0,00	2,84	
10:40:33	0,00	0,00	0,00	2,84	
10:40:43	0,00	0,00	0,00	2,84	
10:40:53	0,00	0,00	346	2,84	
10:41:03	12,30	0,00	326	2,84	
10:41:13	12,00	0,00	326	2,84	
10:41:23	12,00	0,00	326	2,84	
10:41:33	11,90	0,00	326	2,84	
10:41:43	12,10	0,00	326	2,84	
10:41:53	12,10	0,00	326	2,84	
10:42:03	12,00	0,00	326	2,84	
10:42:13	12,00	0,00	326	2,84	
10:42:23	11,90	0,00	326	2,84	
10:42:33	12,30	0,00	326	2,84	
10:42:43	12,20	0,00	326	2,84	
10:42:53	12,10	0,00	326	2,84	
10:43:03	12,10	0,00	326	2,84	
10:43:13	12,00	0,00	328	2,84	
10:43:33	0,00	3,61	310	2,81	
10:44:03	0,00	4,71	310	2,78	
10:44:33	0,00	4,65	308	2,72	
10:45:03	0,00	4,65	316	2,72	
10:45:33	0,00	4,62	326	2,63	
10:46:03	0,00	4,19	312	2,75	
10:46:33	0,00	4,65	308	2,78	
10:47:03	0,00	4,68	310	2,75	
10:47:33	0,00	4,68	318	2,72	
10:48:03	0,00	4,62	308	2,69	
10:48:33	0,00	4,65	314	2,60	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
10:49:03	0,00	4,65	310	2,78	
10:49:33	0,00	4,62	312	2,75	
10:50:03	0,00	4,65	314	2,72	
10:50:33	0,00	4,68	308	2,66	
10:51:03	0,00	4,65	310	2,75	
10:51:33	0,00	4,65	310	2,78	
10:52:03	0,00	4,77	310	2,75	
10:52:33	0,00	4,65	312	2,72	
10:53:03	0,00	4,77	310	2,66	
10:53:33	0,00	4,65	310	2,75	
10:54:03	0,00	4,65	310	2,78	
10:54:33	0,00	4,74	310	2,75	
10:55:03	0,00	4,65	318	2,69	
10:55:33	0,00	4,62	310	2,66	
10:56:03	0,00	4,65	316	2,78	
10:56:33	0,00	4,62	310	2,78	
10:57:03	0,00	4,65	308	2,75	
10:57:33	0,00	4,65	310	2,72	
10:58:03	0,00	4,68	310	2,63	
10:58:33	0,00	4,62	310	2,81	
10:59:03	0,00	4,65	308	2,78	
10:59:33	0,00	4,65	308	2,69	
11:00:03	0,00	4,65	308	2,66	
11:00:33	0,00	4,62	310	2,66	
11:01:03	0,00	4,71	310	2,81	
11:01:33	0,00	4,65	308	2,75	
11:02:03	0,00	4,65	310	2,72	
11:02:33	0,00	4,65	310	2,66	
11:03:03	0,00	4,65	308	2,66	
11:03:33	0,00	4,65	308	2,84	
11:04:03	0,00	4,62	314	2,75	
11:04:33	0,00	4,62	318	2,72	
11:05:03	0,00	4,65	308	2,66	
11:05:33	0,00	4,62	310	2,63	
11:06:03	0,00	4,65	310	2,81	
11:06:33	0,00	4,65	314	2,75	
11:07:03	0,00	4,77	310	2,72	
11:07:33	0,00	4,77	308	2,69	
11:08:03	0,00	4,65	308	2,69	
11:08:33	0,00	4,65	310	2,81	
11:09:03	0,00	4,74	308	2,75	
11:09:33	0,00	4,62	308	2,69	
11:10:03	0,00	4,74	308	2,66	
11:10:33	0,00	4,62	310	2,72	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
11:11:03	0,00	4,62	318	2,78	
11:11:33	0,00	4,74	310	2,75	
11:12:03	0,00	4,68	308	2,72	
11:12:33	0,00	4,65	308	2,66	
11:13:03	0,00	4,62	310	2,75	
11:13:33	0,00	4,74	310	2,78	
11:14:03	0,00	4,62	308	2,75	
11:14:33	0,00	4,68	310	2,72	
11:15:03	0,00	4,62	310	2,69	
11:15:33	0,00	4,65	316	2,75	
11:16:03	0,00	4,65	308	2,78	
11:16:33	0,00	4,65	308	2,75	
11:17:03	0,00	4,62	310	2,69	
11:17:33	0,00	4,62	310	2,63	
11:18:03	0,00	4,71	308	2,81	
11:18:33	0,00	4,65	308	2,78	
11:19:03	0,00	4,71	308	2,72	
11:19:33	0,00	4,65	308	2,69	
11:20:03	0,00	4,65	308	2,63	
11:20:33	0,00	4,62	310	2,81	
11:21:03	0,00	4,65	308	2,78	
11:21:33	0,00	4,71	308	2,72	
11:22:03	0,00	4,71	308	2,66	
11:22:33	0,00	4,65	308	2,63	
11:23:03	0,00	4,77	308	2,81	
11:23:33	0,00	4,74	308	2,75	
11:24:03	0,00	4,65	308	2,72	
11:24:33	0,00	4,65	310	2,66	
11:25:03	0,00	4,74	308	2,63	
11:25:33	0,00	4,65	316	2,78	
11:26:03	0,00	4,62	316	2,72	
11:26:33	0,00	4,77	308	2,69	
11:27:03	0,00	4,62	308	2,66	
11:27:33	0,00	4,65	305	2,69	
11:28:03	0,00	4,62	310	2,78	
11:28:33	0,00	4,62	308	2,75	
11:29:03	0,00	4,65	308	2,69	
11:29:33	0,00	4,62	308	2,69	
11:30:03	0,00	4,62	308	2,75	
11:30:33	0,00	4,65	308	2,78	
11:31:03	0,00	4,65	308	2,75	
11:31:33	0,00	4,62	310	2,72	
11:32:03	0,00	4,77	308	2,69	
11:32:33	0,00	4,65	318	2,75	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
11:33:03	0,00	4,68	305	2,78	
11:33:33	0,00	4,65	314	2,75	
11:34:03	0,00	4,62	318	2,69	
11:34:33	0,00	4,65	308	2,63	
11:35:03	0,00	4,62	305	2,78	
11:35:33	0,00	4,65	310	2,78	
11:36:03	0,00	4,65	308	2,75	
11:36:33	0,00	4,65	308	2,69	
11:37:03	0,00	4,87	308	2,66	
11:37:33	0,00	4,59	314	2,78	
11:38:03	0,00	4,74	308	2,78	
11:38:33	0,00	4,77	308	2,75	
11:39:03	0,00	4,87	308	2,69	
11:39:33	0,00	4,65	308	2,63	
11:40:03	0,00	4,62	310	2,60	
11:40:33	0,00	4,71	308	2,84	
11:41:03	0,00	4,65	308	2,81	
11:41:33	0,00	4,65	308	2,75	
11:42:03	0,00	4,65	308	2,69	
11:42:33	0,00	4,65	310	2,66	
11:43:03	0,00	4,77	308	2,63	
11:43:33	0,00	4,65	316	2,57	
11:44:03	0,00	4,74	310	2,78	
11:44:33	0,00	4,62	318	2,75	
11:45:03	0,00	4,65	308	2,72	
11:45:33	0,00	4,65	310	2,66	
11:46:03	0,00	4,65	308	2,63	
11:46:33	0,00	4,62	308	2,57	
11:47:03	0,00	4,62	334	2,78	
11:47:33	0,00	4,71	308	2,78	
11:48:03	0,00	4,71	305	2,72	
11:48:33	0,00	4,62	308	2,66	
11:49:03	0,00	4,71	308	2,66	
11:49:33	0,00	4,65	312	2,57	
11:50:03	0,00	4,65	316	2,78	
11:50:33	0,00	4,62	318	2,78	
11:51:03	0,00	4,65	308	2,75	
11:51:33	0,00	4,74	308	2,69	
11:52:03	0,00	4,62	308	2,63	
11:52:33	0,00	4,62	308	2,60	
11:53:03	0,00	4,65	316	2,69	
11:53:33	0,00	4,74	308	2,84	
11:54:03	0,00	4,62	308	2,75	
11:54:33	0,00	4,65	308	2,75	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
11:55:03	0,00	4,74	308	2,69	
11:55:33	0,00	4,62	310	2,66	
11:56:03	0,00	0,00	0,00	2,63	
11:56:33	0,00	0,00	0,00	2,63	
11:57:03	0,00	0,00	0,00	2,63	

Time hh:mm:ss	Xe Feed Unit Input	Primary Xe Feed Branch	Redundant Xe Feed Branch	Xe Storage Unit 1	Xe Storage Unit 2	Xe Storage Unit 3	Xe Feed Unit	Thruster Unit 2
	Pressure (kgf/cm ²)			Temperature (°C)				
10:31:04	55,05	4,67	4,02	11,15	11,15	11,15	14,24	9,36
11:04:51	55,05	4,67	4,02	11,15	11,15	11,15	16,86	9,36
11:46:24	55,05	4,74	4,02	11,15	11,15	11,15	16,86	9,36
11:49:37	55,05	4,67	4,02	11,15	11,15	11,15	16,86	9,36
11:50:46	55,05	4,67	4,02	11,15	11,15	11,15	16,86	12,69
11:52:48	55,05	4,59	4,02	11,15	11,15	11,15	16,86	12,69

Annex 9. RT4C2 Thruster Operation TM-data based on available TM-data receipt sessions (31/03/01)

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
09:01:33	0,00	0,00	0,00	2,51	
09:01:43	0,00	0,00	0,00	2,51	
09:01:53	0,00	0,00	0,00	2,51	
09:02:03	0,00	0,00	0,00	2,51	
09:02:13	0,00	0,00	0,00	2,51	
09:02:23	0,00	0,00	0,00	2,60	
09:02:33	0,00	0,00	0,00	2,72	
09:02:43	0,00	0,00	0,00	2,81	
09:02:53	0,00	0,00	0,00	2,84	
09:03:03	0,00	0,00	0,00	2,84	
09:03:13	0,00	0,00	0,00	2,84	
09:03:23	0,00	0,00	0,00	2,84	
09:03:33	0,00	0,00	0,00	2,84	
09:03:43	0,00	0,00	0,00	2,84	
09:03:53	0,00	0,00	0,00	2,84	
09:04:03	0,00	0,00	0,00	2,84	
09:04:13	0,00	0,00	346	2,84	
09:04:23	11,90	0,00	322	2,84	
09:04:33	12,00	0,00	322	2,84	
09:04:43	12,00	0,00	322	2,84	
09:04:53	12,30	0,00	322	2,84	
09:05:03	12,20	0,00	322	2,84	
09:05:13	12,10	0,00	322	2,84	
09:05:23	12,00	0,00	322	2,84	
09:05:33	12,00	0,00	322	2,84	
09:05:43	11,90	0,00	322	2,84	
09:05:53	11,90	0,00	322	2,84	
09:06:03	12,00	0,00	322	2,84	
09:06:13	12,00	0,00	322	2,84	
09:06:23	12,00	0,00	322	2,84	
09:06:33	12,00	0,00	322	2,84	
09:06:43	12,00	0,00	322	2,84	
09:06:53	0,00	3,49	312	2,81	
09:07:23	0,00	4,68	308	2,75	
09:07:53	0,00	4,59	308	2,72	
09:08:23	0,00	4,65	308	2,66	
09:08:53	0,00	4,65	308	2,63	
09:09:23	0,00	4,22	310	2,63	
09:09:53	0,00	4,71	305	2,84	
09:10:23	0,00	4,62	310	2,78	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
09:10:53	0,00	4,71	308	2,75	
09:11:23	0,00	4,62	308	2,72	
09:11:53	0,00	4,65	308	2,66	
09:12:23	0,00	4,62	305	2,63	
09:12:53	0,00	4,62	305	2,78	
09:13:23	0,00	4,65	310	2,75	
09:13:53	0,00	4,59	310	2,72	
09:14:23	0,00	4,65	305	2,69	
09:14:53	0,00	4,71	308	2,66	
09:15:23	0,00	4,62	308	2,66	
09:15:53	0,00	4,65	314	2,69	
09:16:23	0,00	4,65	308	2,84	
09:16:53	0,00	4,62	310	2,78	
09:17:23	0,00	4,65	308	2,75	
09:17:53	0,00	4,62	308	2,69	
09:18:23	0,00	4,65	318	2,63	
09:18:53	0,00	4,62	318	2,60	
09:19:23	0,00	4,65	316	2,84	
09:19:53	0,00	4,62	308	2,78	
09:20:23	0,00	4,62	310	2,75	
09:20:53	0,00	4,62	308	2,69	
09:21:23	0,00	4,65	310	2,66	
09:21:53	0,00	4,62	308	2,63	
09:22:23	0,00	4,62	305	2,75	
09:22:53	0,00	4,62	310	2,84	
09:23:23	0,00	4,65	312	2,75	
09:23:53	0,00	4,65	308	2,72	
09:24:23	0,00	4,71	308	2,66	
09:24:53	0,00	4,59	308	2,63	
09:25:23	0,00	4,62	305	2,63	
09:25:53	0,00	4,65	314	2,84	
09:26:23	0,00	4,65	308	2,78	
09:26:53	0,00	4,62	308	2,75	
09:27:23	0,00	4,65	314	2,72	
09:27:53	0,00	4,62	308	2,66	
09:28:23	0,00	4,65	318	2,63	
09:28:53	0,00	4,62	308	2,75	
09:29:23	0,00	4,62	308	2,84	
09:29:53	0,00	4,65	308	2,75	
09:30:23	0,00	4,65	308	2,72	
09:30:53	0,00	4,62	308	2,66	
09:31:23	0,00	4,65	310	2,63	
09:31:53	0,00	4,68	305	2,69	
09:32:23	0,00	4,59	308	2,84	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
09:32:53	0,00	4,65	308	2,78	
09:33:23	0,00	4,59	310	2,75	
09:33:53	0,00	4,68	308	2,69	
09:34:23	0,00	4,65	308	2,66	
09:34:53	0,00	4,62	308	2,60	
09:35:23	0,00	4,77	308	2,81	
09:35:53	0,00	4,62	310	2,81	
09:36:23	0,00	4,62	308	2,75	
09:36:53	0,00	4,62	308	2,69	
09:37:23	0,00	4,65	318	2,66	
09:37:53	0,00	4,62	308	2,63	
09:38:23	0,00	4,65	316	2,72	
09:38:53	0,00	4,62	308	2,84	
09:39:23	0,00	4,62	318	2,78	
09:39:53	0,00	4,65	310	2,72	
09:40:23	0,00	4,74	310	2,66	
09:40:53	0,00	4,62	308	2,63	
09:41:23	0,00	4,62	314	2,63	
09:41:53	0,00	4,62	308	2,84	
09:42:23	0,00	4,65	308	2,81	
09:42:53	0,00	4,62	318	2,75	
09:43:23	0,00	4,62	308	2,69	
09:43:53	0,00	4,65	310	2,66	
09:44:23	0,00	4,65	310	2,63	
09:44:53	0,00	4,65	305	2,57	
09:45:23	0,00	4,65	308	2,84	
09:45:53	0,00	4,65	310	2,81	
09:46:23	0,00	4,77	308	2,75	
09:46:53	0,00	4,65	308	2,72	
09:47:23	0,00	4,62	308	2,66	
09:47:53	0,00	4,59	310	2,66	
09:48:23	0,00	4,62	308	2,57	
09:48:53	0,00	4,65	314	2,84	
09:49:23	0,00	4,65	310	2,78	
09:49:53	0,00	4,65	308	2,75	
09:50:23	0,00	4,68	308	2,72	
09:50:53	0,00	4,65	308	2,69	
09:51:23	0,00	4,65	308	2,63	
09:51:53	0,00	4,65	308	2,57	
09:52:23	0,00	4,59	308	2,78	
09:52:53	0,00	4,62	308	2,84	
09:53:23	0,00	4,71	308	2,75	
09:53:53	0,00	4,65	308	2,69	
09:54:23	0,00	4,65	308	2,66	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
09:54:53	0,00	4,65	308	2,63	
09:55:23	0,00	4,62	308	2,57	
09:55:53	0,00	4,77	308	2,81	
09:56:23	0,00	4,62	308	2,84	
09:56:53	0,00	4,62	308	2,75	
09:57:23	0,00	4,65	310	2,72	
09:57:53	0,00	4,62	308	2,66	
09:58:23	0,00	4,62	310	2,63	
09:58:53	0,00	4,65	308	2,81	
09:59:23	0,00	4,65	314	2,75	
09:59:53	0,00	4,68	308	2,72	
10:00:23	0,00	4,62	308	2,66	
10:00:53	0,00	4,59	310	2,66	
10:01:23	0,00	4,68	310	2,84	
10:01:53	0,00	4,62	308	2,75	
10:02:23	0,00	4,62	308	2,69	
10:02:53	0,00	4,65	308	2,66	
10:03:23	0,00	4,65	314	2,63	
10:03:53	0,00	4,71	308	2,84	
10:04:23	0,00	4,62	308	2,75	
10:04:53	0,00	4,65	308	2,72	
10:05:23	0,00	4,62	308	2,69	
10:05:53	0,00	4,65	308	2,66	
10:06:23	0,00	4,62	308	2,57	
10:06:53	0,00	4,62	310	2,81	
10:07:23	0,00	4,65	310	2,78	
10:07:53	0,00	4,62	308	2,75	
10:08:23	0,00	4,65	308	2,72	
10:08:53	0,00	4,77	308	2,66	
10:09:23	0,00	4,62	310	2,63	
10:09:53	0,00	4,65	308	2,72	
10:10:23	0,00	4,68	310	2,84	
10:10:53	0,00	4,62	310	2,78	
10:11:23	0,00	4,65	308	2,75	
10:11:53	0,00	4,62	308	2,69	
10:12:23	0,00	4,71	308	2,63	
10:12:53	0,00	4,65	308	2,60	
10:13:23	0,00	4,71	308	2,84	
10:13:53	0,00	4,65	308	2,81	
10:14:23	0,00	4,68	308	2,75	
10:14:53	0,00	4,65	308	2,72	
10:15:23	0,00	4,65	308	2,66	
10:15:53	0,00	4,62	308	2,63	
10:16:23	0,00	4,62	305	2,57	

Time, hh:mm:ss	Cathode Current, A	Anode Current, A	Anode Voltage, V	Xe Feed Unit Output, (kgf/sm ²)	Comments
10:16:53	0,00	4,65	308	2,84	
10:17:23	0,00	4,62	308	2,81	
10:17:53	0,00	4,68	308	2,75	
10:18:23	0,00	4,74	308	2,72	
10:18:53	0,00	4,62	308	2,66	
10:19:23	0,00	4,62	308	2,63	
10:19:53	0,00	4,62	305	2,57	
10:20:23	0,00	4,77	308	2,84	
10:20:53	0,00	4,62	310	2,81	
10:21:23	0,00	4,65	314	2,72	
10:21:53	0,00	4,65	308	2,72	
10:22:23	0,00	4,65	308	2,66	
10:22:53	0,00	4,65	308	2,66	
10:23:23	0,00	4,74	308	2,57	
10:23:53	0,00	4,71	308	2,81	
10:24:23	0,00	4,59	310	2,81	
10:24:53	0,00	4,62	305	2,75	
10:25:23	0,00	4,65	310	2,69	
10:25:53	0,00	4,65	308	2,66	
10:26:23	0,00	4,65	314	2,63	
10:26:53	0,00	4,65	318	2,57	
10:27:23	0,00	4,65	308	2,78	
10:27:53	0,00	4,65	318	2,84	
10:28:23	0,00	4,62	308	2,75	
10:28:53	0,00	4,68	305	2,72	
10:29:23	0,00	4,62	308	2,66	
10:29:53	0,00	4,68	305	2,63	
10:30:23	0,00	4,68	310	2,57	
10:30:53	0,00	4,59	310	2,78	
10:31:23	0,00	4,59	308	2,84	
10:31:53	0,00	0,00	0,00	2,81	

Time hh:mm:ss	Xe Feed Unit Input	Primary Xe Feed Branch	Redundant Xe Feed Branch	Xe Storage Unit 1	Xe Storage Unit 2	Xe Storage Unit 3	Xe Feed Unit	Thruster Unit 4
	Pressure (kgf/cm ²)			Temperature (°C)				
09:01:24	55,05	4,59	4,02	10,63	10,63	9,58	13,19	7,36
09:10:28	55,05	4,95	4,02	10,63	10,63	9,58	13,19	7,36
09:52:50	55,05	4,95	4,02	10,63	10,63	9,58	13,19	10,69
10:00:21	55,05	4,95	4,02	10,63	10,63	9,58	15,81	10,69
10:23:39	55,05	4,67	4,02	10,63	10,63	9,58	15,81	10,69
10:30:41	55,05	4,59	4,02	10,63	10,63	9,58	15,81	10,69

REPORT DOCUMENTATION PAGE			Form Approved OMB No. 0704-0188	
Public reporting burden for this collection of information is estimated to average 1 hour per response, including the time for reviewing instructions, searching existing data sources, gathering and maintaining the data needed, and completing and reviewing the collection of information. Send comments regarding this burden estimate or any other aspect of this collection of information, including suggestions for reducing this burden, to Washington Headquarters Services, Directorate for Information Operations and Reports, 1215 Jefferson Davis Highway, Suite 1204, Arlington, VA 22202-4302, and to the Office of Management and Budget, Paperwork Reduction Project (0704-0188), Washington, DC 20503.				
1. AGENCY USE ONLY (Leave blank)		2. REPORT DATE June 2003		3. REPORT TYPE AND DATES COVERED Final Contractor Report
4. TITLE AND SUBTITLE Hall Effect Thruster Interactions Data From the Russian Express-A2 and Express-A3 Satellites Acquire Express-A3 SPT-100 Based Propulsion Subsystem and Other Subsystem Flight Operation TM-Data for the Period of January 1, 2001 to and Including March 31, 2001, Task 32			5. FUNDING NUMBERS WBS-22-800-91-01 NAS3-99151 NAS3-99204	
6. AUTHOR(S) N. Sitnikova, D. Volkov, I. Maximov, V. Petrusevich, and D. Allen				
7. PERFORMING ORGANIZATION NAME(S) AND ADDRESS(ES) Nauchno-Proizvodstvennoe Obiedinenie Prikladnoi Mekhaniki (NPO PM) 52 Lenin Street, Zheleznogorsk-2 Krasnoyarsk region, 662990, Russia			8. PERFORMING ORGANIZATION REPORT NUMBER E-13691-7	
9. SPONSORING/MONITORING AGENCY NAME(S) AND ADDRESS(ES) National Aeronautics and Space Administration Washington, DC 20546-0001			10. SPONSORING/MONITORING AGENCY REPORT NUMBER NASA CR-2003-212005-PART7	
11. SUPPLEMENTARY NOTES N. Sitnikova, D. Volkov, I. Maximov, and V. Petrusevich, Nauchno-Proizvodstvennoe Obiedinenie Prikladnoi (NPO PM) 52 Lenin Street, Zheleznogorsk-2, Mekhaniki, Krasnoyarsk region, 662990, Russia. D. Allen, Schafer Corporation, 321 Billerica Road, Chelmsford, Massachusetts 01824-4191. Project Manager, John Dunning, Power and Propulsion Office, NASA Glenn Research Center, organization code 6900, 216-433-5298.				
12a. DISTRIBUTION/AVAILABILITY STATEMENT Unclassified - Unlimited Subject Category: 20 Available electronically at http://gltrs.grc.nasa.gov This publication is available from the NASA Center for AeroSpace Information, 301-621-0390.			12b. DISTRIBUTION CODE	
13. ABSTRACT (Maximum 200 words) This 12-part report documents the data obtained from various sensor measurements taken aboard the Russian Express-A2 and Express-A3 spacecraft in Geosynchronous Earth Orbit (GEO). These GEO communications satellites, which were designed and built by NPO Prikladnoy Mekhaniki (NPO PM) of Zheleznogorsk, Russia, utilize Hall thruster propulsion systems for north-south and east-west stationkeeping and as of June 2002, were still operating at 80° E. and 11° W., respectively. Express-A2 was launched on March 12, 2000, while Express-A3 was launched on June 24, 2000. The diagnostic equipment from which these data were taken includes electric field strength sensors, ion current and energy sensors, and pressure sensors. The diagnostics and the Hall thruster propulsion systems are described in detail along with lists of tabular data from those diagnostics and propulsion system and other satellite systems. Space Power, Inc., now part of Pratt & Whitney's Chemical Systems Division, under contract NAS3-99151 to the NASA Glenn Research Center, obtained these data over several periods from March 12, 2000, through September 30, 2001. Each of the 12 individual reports describe, in detail, the propulsion systems as well as the diagnostic sensors utilized. Finally, parts 11 and 12 include the requirements to which NPO PM prepared and delivered these data.				
14. SUBJECT TERMS Propulsion; Electric propulsion; Hall thrusters; Hall effect			15. NUMBER OF PAGES 69	
			16. PRICE CODE	
17. SECURITY CLASSIFICATION OF REPORT Unclassified	18. SECURITY CLASSIFICATION OF THIS PAGE Unclassified	19. SECURITY CLASSIFICATION OF ABSTRACT Unclassified	20. LIMITATION OF ABSTRACT	